

ECONOMICS LABORATORY,INC. -- STAINLESS STEEL CLEANER AND POLISH -- 7930-00-279-7464

=====
Product Identification
=====

Product ID:STAINLESS STEEL CLEANER AND POLISH

MSDS Date:08/26/1987

FSC:7930

NIIN:00-279-7464

MSDS Number: BBBLB

=== Responsible Party ===

Company Name:ECONOMICS LABORATORY,INC.

City:ST. PAUL

State:MN

ZIP:55102

Country:US

Info Phone Num:1-612-293-2233

Emergency Phone Num:1-800-328

-0026

CAGE:5G570

=== Contractor Identification ===

Company Name:ECOLAB PROFESSIONAL PRODUCTS DIVISION OF ECOLAB INC.

Address:ECOLAB CENTER

Box:City:ST PAUL

State:MN

ZIP:55102

Country:US

Phone:800-352-5326

CAGE:85884

Company Name:ECONOMICS LABORATORY INC

Address:370 WAFASHA ST

City:ST PAUL

State:MN

ZIP:55102

Phone:(612) 293-2233

CAGE:5G570

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS (HEAVY NAPHTHA)

CAS:64475-85-0

RTECS #:PY8240000

Fraction by

Wt: 10%
ACGIH TLV:200

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)
CAS:71-55-6
RTECS #:KJ2975000
Fraction by Wt: 30%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:350 PPM
ACGIH TLV:350 PPM/450STEL;9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:ISOBUTANE (PROPELLANT)
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 5%
ACGIH TLV:2300

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 5%
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN;
9192

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:MAY CAUSE EYE OR SKIN IRRITATION. MAY CAUSE
STOMACH DISTRESS, NAUSEA OR VOMITING IF SWALLOWED. MAY CAUSE
BREATHING DIFFICULTIES,DIZZINESS,HEADACHE OR UNCONSCIOUSNESS.

=====
First Aid Measures
=====

First Aid:IF INHALED,IMMEDIATELY MOVE TO FRESH AIR.EYES:FLUSH WITH
WATER FOR 15 MINUTES. IF S
WALLOWED,RINSE MOUTH,THEN DRINK ONE OR
TWO LARGE GLASSES OF WATER. DO NOT INDUCE VOMITING. SKIN:FLUSH WITH
WATER,THEN WASH WITH SOAP AND WATER. IF IRRITATION OR DISCOMFORT
PERSISTS,CALL A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:165F
Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,FOAM
Fire Fighting Procedures:WATER MAY BE USED TO KEEP FIRE EXPOSED
CONTAINERS COOL BUT MAY BE INEFFECTIVE AS AN EXTINGUISHING AGENT.
Unusual Fire/E

xplosion Hazard:CONTENTS UNDER PRESSURE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE.
AVOID BREATHING VAPORS AND REMOVE WITH INERT ABSORBENT.

===== Handling and Storage =====

Other Precautions:UNMIXED PROPELLANT IS EXTREMELY FLAMMABLE. TO REDUCE
FLAMMABILITY,SHAKE WELL BEFORE USING.

===== Exposure Controls/Personal Protection =====

Ventilat
ion:VENTILATE AS APPROPRIATE FOR AMOUNTS OF SPILL.
Eye Protection:GOGGLES
Supplemental Safety and Health
DO NOT STORE ABOVE 120F. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT
SUNLIGHT OR OTHER HEAT MAY CAUSE BURSTING. DO NOT PUNCTURE OR
INCINERATE. DO NOT SPRAY NEAR FIRE OR OPEN FLAME.

===== Physical/Chemical Properties =====

Solubility in Water:NEGLIGIBLE
Appearance and Odor:AEROSOL.MILD HYDROCARBON ODOR

===== Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE. CONSULT STATE AND LOCAL
AUTHORITIES FOR RESTRICTIONS ON DISPOSAL OF CHEMICAL WASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warr

ants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.