

ESSEX CHEMICAL CORP., SPECIALTY CHEMICALS DIV. -- PRO-SEAL 870 A-2 (BASE) --
8030-00-008-7196

===== Product Identification =====

Product ID:PRO-SEAL 870 A-2 (BASE)

MSDS Date:01/01/1985

FSC:8030

NIIN:00-008-7196

Kit Part:Y

MSDS Number: BCVDG

=== Responsible Party ===

Company Name:ESSEX CHEMICAL CORP., SPECIALTY CHEMICALS DIV.

Address:19451 SUSANA RD

City:COMPTON

State:CA

ZIP:90221-5713

Country:US

CAGE:83527

=== Contractor Identification ===

Company Name:ESSEX CHEMICAL CORP PRO-SEAL DIV

Address:19451 SUSANA RD

Box:City:COMPTON

State:CA

ZIP:90221-5713

Country:US

Phone:310-537-7600

CAGE:83527

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:MERCAPTAN TERMINATED POLYSULFIDE POLYMER

=====

Hazards Identification =====

Effects of Overexposure:MAY CAUSE SKIN OR EYE IRRITATION.

===== First Aid Measures =====

First Aid:SKIN:WASH AFFECTED AREA COPIOUSLY W/WATER. INGESTION:GIVE EMETIC. CALL MD. EYE:IMMEDIATELY FLUSH W/WATER AT LEAST 15 MINUTES. CALL MD.

===== Fire Fighting Measures =====

Flash Point:40 F CC
Lower Limits:1.3
Upper Limits:6.8
Extinguishing Media:CO*2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:WATER NOT RECOMMENDED.
Unusual Fire/Explosion Hazard:PRODUCT CONTAINS VOLATILE SOLVENT.

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP W/RAGS AND SOLVENTS (MFR).

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT INGEST. WASH HANDS THOROUGHLY AFTER HANDLING. STORE BELOW 80F.
Other Precautions:AVOID CONTACT W/SPARK, OPEN FLAME, FLAMMABLE MATERIAL.

===== Exposure Controls/Personal Protection =====

Ventilation:MECHANICALPROVIDE SUFFICIENT VENTILATION
Protective Gloves:RECOMMENDED
Eye Protection:RECOMMENDED
Work Hygienic Practices:PRODUCT CONFORMS TO MIL-S-81733 TYPE I-2. MFR GIVES SEALANT LD50 0.5 TO 5 G/KG ORAL RATS. PART A OF A TWO PART PRODUCT.K
Supplemental Safety and Health
EY1:F3.

===== Physical/Chemical Properties =====

HCC:F3
Boiling Pt:B.P. Text:230F
Vapor Density:3.1
Spec G

ravity:1.31

Evaporation Rate & Reference:1.9 N-BUTYL ACET.

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WHITE SEMI-SOLID FLUID, SULFIDE ODOR.

Percent Volatiles by Volume:15.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:MFR SUGGESTS BURNING. DISPOSE IN ACCORDANCE
W/LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provide

d with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.