

INLAND PACKAGING, INC. -- INNERBOND 2010 FLUID, 12,500 CST. -- 9150-00-024-9624
===== Product Identification =====

Product ID:INNERBOND 2010 FLUID, 12,500 CST.

MSDS Date:01/01/1987

FSC:9150

NIIN:00-024-9624

MSDS Number: BCVPT

=== Responsible Party ===

Company Name:INLAND PACKAGING, INC.

Address:209 PETERSON DRIVE

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Info Phone Num:502-737

-6757

Emergency Phone Num:502-737-6757

CAGE:66172

=== Contractor Identification ===

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phone:502-737-6757

CAGE:66172

===== Composition/Information on Ingredients =====

Ingred Name:POLYDIMETHYLSILOXANE

CAS:9016-00-6

RTECS #:TQ2690000

Fraction by Wt: 100.0%

===== Hazards Identification =====

LD50 LC50 Mixture:LD LO RAT:1500 MG/

KG

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:PER MSDS,THESE FLUIDS ARE
NON-TOXIC;MAY CAUSE MILD TRANSIENT EYE IRRITATION OR SKIN.
CHRONIC:NO DATA AVAILABLE.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS
LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:SEE HEALTH HAZARD DATA.

Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====
===== First Aid Measures =====
=====

First Aid:EYES:FLUSH EYES WITH PLENTY OF WATER;SEEK MEDICAL HELP IF
NEEDED. SKIN:WASH WITH SOAP AND WATER. INHALATION:REMOVE TO FRESH
AIR,CALL A PHYSICIAN IF NEEDED. INGESTION:INDUCE VOMITING IF
CONSCIOUS,SEEK MEDICAL HELP IF NECESSARY.

=====
===== Fire Fighting Measures =====

Flash Point Method:OC

Flash Point:570F/299C

Extinguishing Media:WATER FOG,FOAM,CO*2.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PRO

TECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:NONE NOTED.

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;SWEEP WITH
SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AREA;KEEP AWAY FROM
HEAT,MOISTURE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NEEDED IF THERE IS AN ADEQUATE VENTILATION.

Ventilation:LOCAL EXHAUST/GENERAL TO MAINTAIN AN ADEQUATE VENTILATION.

Protective Gloves:IMPERVIOUS.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:WORK UNIFORM,EYE WASH.

Work Hygienic Practices:AVOID CONTACT WITH SKIN AND EYE;AVOID BREATHING
VAPORS/MIST;WASH THOROUGHLY AFTER USE.

Supplemental Safety and Health

=====

===== Physical/Chemical Properties =====

HCC:V6

Melt/Freeze Pt:M.P/F.P Text:-49F(FREEZE

Vapor Pres:0.01

Spec Gravity:0.97

Solubility in Water:INSOLUBLE

Appearance and Odor:CLEAR, COLORLESS LIQUID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MINERAL ACID,STRONG BASE.

Stability Condition to Avoid:EXTREME HEAT.

Hazardous Decomposition Products:SILICA MAY BE EMITTED ON COMBUSTION.

===== Disposal

Considerations =====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH
LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
docu

ment should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.