

EASTMAN KODAK COMPANY -- 155 8949,METAL ETCH RESIST DEVELOPER -- 6750-00-032-0622

===== Product Identification =====

Product ID:155 8949,METAL ETCH RESIST DEVELOPER

MSDS Date:01/01/1985

FSC:6750

NIIN:00-032-0622

MSDS Number: BCVSS

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency

Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 45.0%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 55.0%

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

===== Hazards Identification =====

Effects of Overexposure:SKIN:REPTD/PROLNGD LIQ CONTCT CAUSES  
DEFATTNG;EYES:CONTACTW/LIQUID CAUSES IRRITATION\*SEE SUPP DATA\*

===== First Aid Measures =====

First Aid:INH:REMOVE FROM EXPOSURE.GIVE CPR/OXY IF NEEDED & GET MED  
ATTN;EYES:FL  
USH IMMED W/WATER FOR AT LEAST 15 MIN.GET MED  
HELP;SKIN:FLUSH IMMED W/PLENTY OF WATER FOR 15 MIN.FOR IRRIT GET  
MED ATTN.

===== Fire Fighting Measures =====

Flash Point:86F(30C)-TCC

Lower Limits:0.8%

Upper Limits:7.0%

Extinguishing Media:CO\*2,DRY CHEM,DRY FOAM

Fire Fighting Procedures:USE SELF-CONTND BRTHG APP;COOL EXPSD CONT  
W/WATER SPRAY.

Unusual Fire/Explosion Hazard:SPILL/RUNOFF MAY CAUSE  
POLUTION,FIRE/EXPLOSION HAZARD;CONTNRS(EMPTY/FULL)MAY  
EXPLODE IN  
HEAT OF FIRE

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS.ELIM IGN  
SOURCES.USE PROTCTV/SAFETY EQUIP.STOP LEAK W/O RISK.PROVIDE  
VENT.DIKE LG SPILL.PUMP LIQ TOSALVAGE TANK.ABSORB REMAINING LIQ  
W/ABSRBNG MATL & SHOVEL INTO DRUMS;PER MFR SOAK UP SM SPILL  
W/ABSRBNT MATL IAWREGS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY

FROM SOURCE OF IGN.STORE IN  
COOL, DRY, PLACE. KEEP CONTNRS TIGHTLY CLOSED. PROTECT CONTNRS FROM  
PHYSICAL DAMAGE.

Other Precautions: AVOID SKIN/EYE CONTACT W/CHEMICAL PRODUCTS. WASH  
THOROUGHLY AFTER HANDLING USING PLENTY OF WATER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: AN APPRVD ORGANIC VAP RESPIRATOR FOR EMERGENCY  
USE ONLY

Ventilation: LOCAL EXHAUST & MECHANICAL (GENERAL) RECOMMENDED BY MFGR.

Protective Gloves: IMPERVIOUS

Eye Protection

: SAFETY GLASSES/GOGGLES

Other Protective Equipment: AS NECESSARY TO PREVENT SKIN CONTACT.

Supplemental Safety and Health

\*INHALATION EFFECT: PROLONGED EXPOSURE TO HIGH VAP CONC MAY CAUSE  
ANESTHETIC EFFECT ALONG WITH HEADACHE, DIZZ & NAUSEA; MSDS FM MFR  
DTD: 12/15/77

===== Physical/Chemical Properties =====

HCC: F4

Boiling Pt: B.P. Text: 291-360F

Vapor Density: 4

Spec Gravity: 0.8121

Solubility in Water: NEGLIGIBLE

Appearance and Odor: COLORLESS LIQ+ PETROLEUM ODOR

Perce

nt Volatiles by Volume: 100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

OXIDIZING & CORROSIVE MATERIAL

Stability Condition to Avoid: SOURCE OF IGNITION

Hazardous Decomposition Products: BURNING MAY RESULT IN EVOLUTION OF CO  
& CO<sub>2</sub>.

===== Disposal Considerations =====

Waste Disposal Methods: KEEP IN COVERED CONTNRS PENDING DISPOSAL. SHIP  
WASTE MATL IAW DOT TO DISPOSAL/INCINERATING FACILITY. H

HANDLE/DISPOSE

IN FULL COMPLIANCE W/ALL FED ,STATE,LOCAL REGS;MFR

RECOMMENDS:BURN-TREAT AS ORGANICSOL VNTS.FED,ST.& LOCAL EFFLUENT  
LAWS TAKE PRECEDENCE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizi

ng this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.