View NSN Online: https://aerobasegroup.ae/nsn/6830-00-042-8132

CRYODINE SPECIALTY GASES, INC. -- OXYGEN -- 6830-00-042-8132

Product ID:OXYGEN MSDS Date:10/01/1985 FSC:6830 NIIN:00-042-8132 MSDS Number: BCVWN === Responsible Party === Company Name: CRYODINE SPECIALTY GASES, INC. Address:445 STATE STREET **City:NORTH HAVEN** State:CT ZIP:06473 Info Phone Num:203-288-1440 Emergency Phone Num:203-288-1440 CAGE: JO873 === Contractor Iden tification === Company Name: CRYODINE SPECIALTY GASES, INC. Address:445 STATE STREET Box:City:NORTH HAVEN State:CT ZIP:06473 Phone:203-288-1440 CAGE: JO873 Company Name: CRYODYNE TECHNOLOGIES INC Address:67 WINTHROP RD Box:233 City:CHESTER State:CT ZIP:06412 Country:US Phone:203-526-5000 CAGE:0EHW9

Ingred Name:OXYGEN CAS:7782-44-7 RTECS #:RS2060000 Fraction by Wt: 100%

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: HYPEROXIA WHICH LEADS TO PNEUMONIA. Effects of Overexposure:CRAMPS,NAUSEA,DIZZINESS,HYPOTHERMIA,AMBYLOPIA,RESPIRAT ORY DIFFICULTIES, BRADYCARDIA, FAINTING SPELLS & CONVULSIONS CAPABLE OF LEADING TO DEATH. Medical Cond Aggravated by Exposure:NONE NOTED. First Aid:PROMPT MEDICAL ATTENTION IS MANDATORY. REMOVE TO FRESH AIR. IF UNCONSCIOUS GIVE CPR. -RESCUE PERSONNEL SHOULD BE COGNIZANT OF EXTREME FIRE HAZARD ASSOCIATED WITH OXYGEN-RICH ATMOSPHERES-Extinguishing Media:WATER Fire Fighting Procedures: IF POSSIBLE, STOP THE FLOW OF OXYGEN WHICH IS SUPPORTING THE FIRE. Unusual Fire/Explosion Hazard: VIGOROUSLY ACCELERATES COMBUSTION ======= Accidental Release Measures ====== _____ Spill Release Procedures: EVACUATE PERSONNEL. USE PROTECTIVE EQUIPMENT. IF LEAK IS IN PIPES, PURGE WITH INERT GAS. IF LEAK IS IN CONTAINER, CONTACT MANUFACTURER. Handling and Storage Precautions: KEEP VALVE PROTECTION CAPS IN PLACE.DO NOT DRAG, SLIDE OR ROLL CYLINDERS. USE HAND TRUCK. USE PRESSURE REDUCING REGULATOR & CHECK VALVE.DO NOT HEAT CYL. Other Precautions: PROTECT FROM PHYSICAL DAMAGE.STORE IN COO L.DRY WELL VENTILATED AREA, AWAY FROM FLAMMMABLE PRODUCTS. STORE UPRIGHT & SECURED. Ventilation: ADEQUATE VENTILATION TO PREVENT OXYGEN CONCENTRATION OVER 25%. Protective Gloves: AS REQUIRED. ANY MATERIAL. Eye Protection:GOGGLES Other Protective Equipment: SAFETY SHOES, SAFETY SHOWER Supplemental Safety and Health

HCC:G4 Boiling Pt:B.P. Text:-297F,-1 83C Melt/Freeze Pt:M.P/F.P Text:-362F F.P. Vapor Density:1.11 Spec Gravity:1.14 @ B.P. Solubility in Water:NEGLIGIBLE Appearance and Odor:COLORLESS,ODORLESS & TASTELESS GAS.

Stability Indicator/Materials to Avoid:YES ALL FLAMMABLE MATERIALS. Stability Condition to Avoid:TEMPERATURES ABOVE 130F (54C) Hazardous Decomposition Products:NONE

Waste Disposal Method s:DO NOT ATTEMPT TO DISPOSE OF RESIDUAL OR UNUSED QUANTITIES. RETURN TO MANUFACTURER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.