

WACKER SILICONE CORP -- SSILICONE FLUID SWS-101 -- 9150-00-066-2382

=====
Product Identification
=====

Product ID:SSILICONE FLUID SWS-101
MSDS Date:05/07/1990
FSC:9150
NIIN:00-066-2382
MSDS Number: BCXBQ
=== Responsible Party ===
Company Name:WACKER SILICONE CORP
Address:3301 SUTTON RD
City:ADRIAN
State:MI
ZIP:49221
Country:US
Info Phone Num:517-263-5711
Emergency Phone Num:517-263-5711
CAGE:4M768

=== Contractor Identification ===
Company Name:WACKER SILICONE CORP
Address:3301 SUTTON RD
City:ADRIAN
State:MI
ZIP:49221
Country:US
Phone:517-263-5711
CAGE:4M768

=====
Composition/Information on Ingredients
=====

Ingred Name:POLYDIMETHYLSILOXANE
CAS:9016-00-6
RTECS #:TQ2690000
Fraction by Wt: 100.0%
Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

LD50 LC50 Mixture:LD 50 FEMALE RAT>34,600 MG/KG
Routes of Entry: Inhalatio

n:UNKNOWN Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:N/RTE:PER MSDS MATERIAL IS NONE
TOXIC.MAY CAUSE TEMPORARY EYE IRRITATION.
Explanation of Carcinogenicity:DATA PER MGF MSDS.
Effects of Overexposure:MAY CAUSE TEMPORARY EYE IRRITATION.
Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE
WORSEN.

=====
First Aid Measures
=====

First Aid:EYES AND SKIN:FLUSH WITH LARGE
AMOUNT OF WATER FOR ABOUT
15-20 MINUTES;SEEK MEDICAL ATTENTION IMMEDIATELY.INHALATION:REMOVE
TO FRESH AIR;CALL A PHYSICIAN.INGESTION:SEEK MEDICAL ATTENTION
IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method:PMCC
Flash Point:>460F,>238C
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMIC
AL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:NONE EXPECTED

=====
Accidental Release Measures
=====

Spill Release Procedures:SCOOP UP GROSS QTY. COVER SUFACE WITH A DRY
POWDER,BRUSH BACK & FORTH,SWEEP UP.REMOVE REMAINING DUST OR POWDER
WITH A SAWDUST-TYPE SWEEPING COMPOUND.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL V
ENTILATED
AREA.KEEP CONTAINER CLOSED WHEN NOT IN USE.
Other Precautions:CLEAN UP SPILLS COMPLETELY AS RESIDUE IS SLIPPERY.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE NORMALLY REQUIRED IF USED WITH ADEQUATE
VENTILATION.
Ventilation:NORMAL ROOM VENTILATION.
Protective Gloves:AS REQUIRED
Eye Protection:SAFETY GLASSES/GOGGLES
Other Protective Equipment:APRON, EYE-WASH FACILITIES
Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO

NOT BREATHE

VAPORS/MIST/DUST.WASH THOROUGHLY AFTER EACH USE.

Supplemental Safety and Health

CLEAN UP SPILLS COMPLETELY AS RESIDUE IS SLIPPERY.VISCOSITY GRADE IS
1.0 CST.

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres: