

FISKE BROTHERS REFINING COMPANY -- LUBRIPLATE 930-AAA;GREASE -- 9150-00-074-5900
===== Product Identification =====

Product ID:LUBRIPLATE 930-AAA;GREASE

MSDS Date:05/01/1987

FSC:9150

NIIN:00-074-5900

MSDS Number: BCXLB

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING COMPANY

Address:129 LOCKWOOD STREET

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-9150

Emerge

ncy Phone Num:201-589-9150

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL(NOT SPECIFIED)

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3

Ingred Name:INORGANIC THICKENER

Ingred Name:ADDITIVES

CAS:24937-78-8

Fraction by Wt: NO

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: EYE:MAY BE MILDLY IRRITATING.
SKIN:RELEASE DURING HIGH PRESSURE USAGE MAY RESULT IN INJECTION OF
OIL INTO THE SKIN CAUSING IRRITATION.INHALATION:NOT EXPECTED TO BE
A RELEVANT ROUTE
OF EXPOSURE; HIGH TEMPERATURE VAPORS IRRITATE
RESPIRATORY TRACT. INGESTION:LOW LEVEL OF TOXICITY. CHRONIC: NO
DATA PER MSDS
Explanation of Carcinogenicity:PER MSDS
Effects of Overexposure:EYE:CONTACT MAY IRRITATE; SKIN:PROLNGD/RPTD.
CONTACT MAY IRRITAT;INGEST: LOW ORDER ACUTE ORAL TOXITY
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE
AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:
NHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING IS
DIFFICULT. GET MEDICAL ATTENTION. EYE: FLUSH WITH WATER FOR 15
MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN:
WASH WITH S OAP & WATER/WATERLESS CLEANER. REMOVE CONTAMINATED
CLOTHING. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. INGESTION:
DO NOT INDUCE VOMITING. IN GENERAL, NO TREATMENT IS REQUIRED. GET
MEDICAL ADVICE.

=====
===== Fire Fighting Measures =====

Flas
h Point Method:COC
Flash Point:400F,204C
Lower Limits:0.9
Upper Limits:7.0
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER
FOG.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:DONOT STORE/MIX W/STRONG OXIDANTS. EMPTY
CONTAINERS RETAIN RESIDUE; DONOT CUT, DRILL,/WELD!!

=====
===== Accid

ental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE,WASH REMAINDER W/SUITABLE PETROL. SOLVENT OR ADD ABSORBENT. KEEP PETROL. PRDS. OUT OF SEWERS & WATER COURSES. ADVISE IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS & WATER COURSES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. KEEP AWAY FROM OPEN FLAMES & HIGH TEMPERATURES.

Other Precautions:AVOID BREATHING OIL MIST. REMOVE OIL-SOAKED CLOTHING & LAUNDRY BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT.

Ventilation:LOCAL EXHAUST TO ELIMINATE MISTS/FUMES/GASES.

Protective Gloves:NEOPRENE RUBBER AS REQUIRED.

Eye Protection

n:SAFETY GLASSES RECOMMENDED.

Other Protective Equipment:EYE WASH STATION,CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

DO NOT GET IN EYES OR ON CLOTHING.MSDS IS ALSO FOR #930-A,930-2,930-AA

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F,>288C

Melt/Freeze Pt:M.P/F.P Text:SE

MI-SOLID

Vapor Pres:5.0

Spec Gravity:0.94-0.97

Evaporation Rate & Reference: