View NSN Online: https://aerobasegroup.ae/nsn/8010-00-078-6070

Product ID:TT-E-489F ENAMEL MSDS Date:01/01/1985 FSC:8010 NIIN:00-078-6070 MSDS Number: BCXNV === Responsible Party === Company Name: AERVOE PACIFIC CO Emergency Phone Num:415-351-4860 CAGE:AERVE === Contractor Identification === Company Name: AERVOE PACIFIC CO INC Address:1198 SAWMILL RD Box:City:GARDNERVIL LE State:NV ZIP:89410 Country:US Phone:702-782-0100 CAGE:AERVE Company Name: FEDERAL SPECIFICATIONS, PROMULGATED BY GSA Box:City:WASHINGTON State:DC Country:US CAGE:81348

Ingred Name:ISOBUTANE RTECS #:NP7700000 Fraction by Wt: 18% ACGIH TLV:500 PPM

Ingred Name:PROPANE CAS:74-98-6 RTECS #:TX2275000 Fraction by Wt: 18% OSHA PEL:1000 PPM ACGIH TLV:ASPHYXIANT; 9192

Ingred Name:ALIPHATIC THINNER Fraction by Wt: 8% ACGIH TLV:500 P ΡM

Ingred Name:ACETONE (SARA III) CAS:67-64-1 RTECS #:AL3150000 Fraction by Wt: 36% OSHA PEL:1000PPM ACGIH TLV:750PPM/1000STEL;9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 20% OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Effects of Overexposure: IRRITATION OF EYES & RESPIR. TRACT. POSSIBLE HEADA CHE & DIZZINESS.

First Aid:FUMES-MOVE TO FRESH AIR; RESTORE BREATHING; GET MED AID. EYE: FLUSH THOROUGHLY W WATER; GET MED AID.

Flash Point:-20F,-29C Lower Limits:1.0 Extinguishing Media:CO2,DRY CHEM, FOAM Fire Fighting Procedures:WATER MAY BE INEFFECTIVE USE TO COOL CONTAINERS Unusual Fire/Explosion Hazard:KEEP FROM HEAT, SPARKS OR OPEN FLAME.

CLOSED CONTAINER MAY EXPLODE IF EXPOSED TO ECTREME HEAT.
======================================
Spill Release Procedures: ELIMATE IGNITION SOURCES-VENTILATE AREA.
======================================
<ul> <li>Handling and Storage Precautions:STORE BELOW 120F. KEEP AWAY FROM HEAT &amp; OPEN FLAME.</li> <li>Other Precautions:AVOID INHALATION OF SPRAY MIST. DO NOT TAKE INTERNALLY</li> </ul>
======== Exposure Controls/Personal Protection ====================================
Respiratory Protection:PAINT SPRAY MASK Ventilation:TO KEEP VAPORS BELOW TLV Supplemental Safety and Health
======================================
HCC:F2 Boiling Pt:B.P. Text:-20F,-29C Vapor Density:>1 Spec Gravity:0.9 Evaporation Rate & amp; Reference:10 Solubility in Water:NONE
======================================
Stability Indicator/Materials to Avoid:YES
======================================
Waste Disposal Methods:IN ACCORD W LOC REGS. DO NOT INCINERATE CLOSED CONTAINERS.
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume r esponsibility for the suitability of this information to their particular situation.