

BORDENK INC., KRYLON DEPT -- KRYLON 1501 GLOSSY WHITE (NEW FORMULA) --
8010-00-079-3762

=====
===== Product Identification =====

Product ID:KRYLON 1501 GLOSSY WHITE (NEW FORMULA)

MSDS Date:01/01/1987

FSC:8010

NIIN:00-079-3762

MSDS Number: BCXRK

=== Responsible Party ===

Company Name:BORDENK INC., KRYLON DEPT

Address:180 E BROAD ST

City:COLUMBUS

State:OH

ZIP:43215-3705

Country:US

CAGE:JO999

=== Contract

or Identification ===

Company Name:BORDEN CHEMICAL CO

Address:180 E BROAD ST

Box:City:COLUMBUS

State:OH

ZIP:43215-3705

Country:US

Phone:614-225-6124

CAGE:86142

Company Name:BORDENK INC., KRYLON DEPT

Address:180 E BROAD ST

Box:City:COLUMBUS

State:OH

ZIP:43215-3705

Country:US

CAGE:JO999

=====
===== Composition/Information on Ingredients =====

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt

Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 8-17%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 6-14%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fra

ction by Wt: 2-3%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 36.5%

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:INH:MAY BE HARMFUL;LIQ/VAP MAY IRRIT
NOSE,THROAT,LUNGS. SKIN/EYES:IRRIT. INGEST:MAY BE HARMFUL

=====

== First Aid Measures =====

First Aid:INGEST:DO NOT INDUCE VOMITING;CALL PHYSICIAN IMMED.

SKIN:IMMED FLUSH W/WATER FOR AT LEAST 15MIN;IF IRRIT PERSISTS,CALL A PHYSICIAN. EYES:IMMED FLUSH W/WATER 15MIN W/EYELIDS APART;CALL MD. INH:REMOVE T O FRESH AIR;GIVE ARTIF RESP OR O*2 IF NEC;CALL MD.

===== Fire Fighting Measures =====

Flash Point:N/A AEROSOL

Extinguishing Media:DRY CHEMICAL,CO*2,FOAM. WATER MAY BE INEFFECTIVE

Fire Fighting

Procedures:USE WATER TO COOL FIRE EXPOS CANS. WEAR SCBA

Unusual Fire/Explosion Hazard:EXTREM FLAM;UNDER PRESSURE. HI TEMP MAY BURST CANS;AVOID ALL HEAT/IGNIT SOURCES,DIRECT SUN.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. SOAK UP

W/ABSORBENT MATERIAL & REMOVE TO A CHEMICAL DISPOSAL AREA. PREVENT ENTRY INTO NATURAL BODIES OF WATER.

===== Handling and Storage =====

H

Handling and Storage Precautions:DO NOT STORE AT TEMPERATUES OVER 120F.

WASH THOROUGHLY AFTER HANDLING. AVOID PROLONGED OR REPEATED CONTACT W/EYES,SKIN OR CLOTHING.

Other Precautions:USE W/ADEQUATE VENTILATION. AVOID BREATHING VAPOR OR MIST. HANDLE IAW GOOD INDUSTRIAL HYGIENE & SAFETY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD RESP PROT DEPENDING ON CONDITIONS OF USE/TLV EXPOS

Ventilation:LOCAL EXHAUST IN VOLUME & PATTERN ADEQ TO KEEP BELOW TLV

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES IF CONTACT LIKELY

Supplemental Safety and Health

DATE OF PREP:06/30/86. ADD INGRED:METHYL ISOBUTYL KETONE,2-4%; 2-PROPANOL 1-METHOXY-,ACETATE,7-8%; PROPANE,16-17%.

===== Physical/Chemical Properties =====

HCC:V3

Vapor Density:>1.0

Spec Gravity: