

D AIRCRAFT PRODUCTS CO. -- DAPCOTAC # 3300 COMP."A" -- 8040-00-097-6524
===== Product Identification =====

Product ID:DAPCOTAC # 3300 COMP."A"
MSDS Date:01/01/1987
FSC:8040
NIIN:00-097-6524
Kit Part:Y
MSDS Number: BCYNM
=== Responsible Party ===
Company Name:D AIRCRAFT PRODUCTS CO.
Address:1191 HAWK CIRCLE
City:ANAHEIM
State:CA
ZIP:92807
Info Phone Num:714-632-8444
Emergency Phone Num:714-632-844
4
CAGE:58093
=== Contractor Identification ===
Company Name:D AIRCRAFT PRODUCTS CO
Address:1191 HAWK CIR
Box:City:ANAHEIM
State:CA
ZIP:92708
Country:US
Phone:714-632-8444
CAGE:58093

===== Composition/Information on Ingredients =====

Ingred Name:SILICONE RUBBER

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 50%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identificati

on =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:DERMATITIS. CONTAINS MUTAGENIC AND
SUSPECTED TERATOGENIC MATERIALS. IRRITANT TO UPPER RESPIRATORY
SYSTEM.
Effects of Overexposure:HEADACHE, NAUSEA, DERMATITIS, UPPER RESPIRATORY
TRACT IRRITATION.
Medical Cond Aggravated by Exposure:SKIN AND RESPIRATORY DISORDERS.

===== First Aid Measures =====
=====

First Aid:IF SWALLOWED, GIVE LARGE AMOUNTS OF WATER. IN CASE OF SKIN OR
EYE CONTACT, WASH THOROUGHLY WITH WATER. IF INHALED, REMOVE TO
FRESH AIR AND IN ALL CASES CALL A PHYSICIAN AS SOON AS POSSIBLE.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:350F,177C
Extinguishing Media:USE FOAM, CO2, WATER FOG, DRY CHEMICALS
Fire Fighting Procedures:DO NOT USE WATER. EXCLUDE AIR. COOL EXPOSED
DRUMS. WEAR SPECIALLY PROTE
CTED OUTFIT. CONSULT LOCAL FIRE STATION.
Unusual Fire/Explosion Hazard:NONE KNOWN

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. WIPE UP WITH
AN INERT MATERIAL. PUT IN A CONTAINER FOR DISPOSAL.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 75 DEG F.
Other Precautions:NONE

===== Exposure Controls/Personal Protect

ion =====

Respiratory Protection:NIOSH APPROVED RESPIRATORY EQUIPMENT.

Ventilation:LOCAL EXHAUST DESIRABLE

Protective Gloves:RUBBER OR POLYETHYLENE

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:NONE

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING OR USE. WASH
CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

KEY1: V5. PART A OF A 2 PART PRODUCT. SEE P/N IND B, THIS NSN, FOR
ADDITIONAL INFORMATION.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:=110.C, 230.F

Vapor Pres:22

Vapor Density:3.2

Evaporation Rate & Reference:2.0 (STD NOT SPECIFIED)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIQUID WITH AN AROMATIC ODOR LIKE BENZENE

Percent Volatiles by Volume:70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS

Stability Condition to Avoid:KEEP FROM HEAT, SPARKS OR ANY SOURCE OF
IGNITION

Hazardous Decomposition

Products:CO, CO2

===== Disposal Considerations =====

Waste Disposal Methods:RECLAIM SOLVENT. DISPOSAL SHOULD BE MADE IN
ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. INCINERATION
IS RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this

information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.