

TRUFLEX RUBBER PRODUCTS CO -- CHEMICAL VULCANIZING CODE 21,PART B --
2640-00-102-0978

===== Product Identification =====

Product ID:CHEMICAL VULCANIZING CODE 21,PART B

MSDS Date:11/22/1985

FSC:2640

NIIN:00-102-0978

Kit Part:Y

MSDS Number: BCYQH

=== Responsible Party ===

Company Name:TRUFLEX RUBBER PRODUCTS CO

Address:1667 N MAIN ST TERMINAL ANNEX

Box:2978

City:LOS ANGELES

State:CA

ZIP:90051

Count

ry:US

Info Phone Num:213-224-6300

Emergency Phone Num:213-224-6300

CAGE:28954

=== Contractor Identification ===

Company Name:TRUFLEX/PANG RUBBER PRODUCTS CO

Address:1667 N MAIN ST

Box:City:LOS ANGELES

State:CA

ZIP:90012

Country:US

Phone:213-224-6300

CAGE:28954

===== Composition/Information on Ingredients =====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 90-97%

Other REC Limits:NONE SPECIFIED

OSHA PEL:350 PPM/4

50 STEL
ACGIH TLV:350 PPM/450STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:NATURAL RUBBER, TACKIFIERS AND ACCELERATORS
Fraction by Wt: 3-8%
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE HAZARDS-EYE CONTACT:IRRITATION.
SKIN:IRRITATION,DERMATITIS
. INHALATION:IRRITATION,CENTRAL NERVOUS
SYSTEM EFFECTS,UNCONSCIOUSNESS,EVEN DEATH. INGESTION:LOW ACUTE
TOXICITY. CHRONIC HAZARDS:LIVER AND KIDNEY DAMAGE.
Explanation of Carcinogenicity:MANUFACTURER STATES NO CARCINOGENIC
INGREDIENTS.
Effects of Overexposure:EYES:PAIN,IRRITATION. SKIN:IRRITATION.
INHALATION:IRRITATION,DIZZINESS,NAUSEA,LIGHTHEADEDNESS,HEADACHE,LOS
S OF EQUILIBRIUM,UNCONSCIOUSNESS,EVEN DEATH. INGESTION:LOW ACUTE
TOXICITY.
Medical Cond Aggravated by Exposure
:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:FIRST AID-EYES:FLUSH WITH WATER FOR AT LEAST 15 MINUTES.
SKIN:WASH WITH SOAP AND WATER WHILE REMOVING CONTAMINATED CLOTHING.
INHALATION:REMOVE TO FRESH AIR.GIVE OXYGEN/CPR IF NEEDED.SEE
DOCTOR. INGESTION:DO NOT INDUCE VOMITING,IF CONSCIOUS,DRINK LARGE
QUANTITIES OF WATER.SEE DOCTOR.

=====
===== Fire Fighting Measures =====

Flash Point:NO
NE
Lower Limits:7.5
Upper Limits:15
Extinguishing Media:WATER FOG
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.
Unusual Fire/Explosion Hazard:CONCENTRATED VAPORS CAN BE IGNITED WITH A
HIGH ENERGY SPARK, FLAME OR OTHER HIGH INTENSITY HEAT SOURCE.
BURNING CAN PRODUCE HCL OR POSSIBLE TRACES OF PHOSGENE.

=====
===== Accidental Release Measure

S =====

Spill Release Procedures:USE APPROPRIATE PROTECTIVE CLOTHING AND EQUIPMENT. ABSORB IN INERT MATERIAL, AND PLACE IN APPROPRIATE DISPOSAL CONTAINER AND SEAL. FLUSH AREA WITH SOAP AND WATER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. KEEP AWAY FROM FLAMES AND IGNITION SOURCES. ALUMINUM IS NOT ACCEPTABLE MATERIAL FOR TANKS, FITTINGS, ETC.

Other Precautions:VAPORS ARE HEAVIER THAN AIR, AND WILL COLLECT IN LOW AREAS. USE SPECIAL BREATHING APPARATUS AND HAVE OBSERVER PRESENT IF ENTERING SUCH AREAS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA-APPROVED ORGANIC VAPOR RESPIRATOR FOR EMERGENCIES.

Ventilation:LOCAL EXHAUST PREFERRED,MECHANICAL EXHAUST ACCEPTABLE.

Protective Gloves:NEOPRENE OR VITON.

Eye Protection:CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO PREVENT

PROLONGED/REPEATED CONTACT. EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH THOROUGHLY AFTER USING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

KEY1:T4. THIS NSN REPRESENTS A KIT WHICH CONSISTS OF 5 PARTS. EACH PART HAS ALSO ITS OWN SEPARATE NSN'S (3 PARTS-PATCHES, 2 PARTS-HAZARDOUS MATERIALS). --ANAESTHETIC EFFECTS MAY BE SEEN IN THE RANGE OF 500-1000 PPM. OVER 1000 PPM MAY CAUSE DIZZINESS. OVER 10000 PPM CAN CAUSE UNCONSCIOUSNESS AND DEATH--.

===== Physical/Chemical Properties =====

HCC:T4

Boiling Pt:B.P. Text:165F/74C

Melt/Freeze Pt:M.P/F.P Text:-49F,-45C

Vapor Pres:100

Vapor Density:4.55

Spec Gravity:1.32

Evaporation Rate & Reference:0.35 (ETHYL ETHER = 1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:TAN LIQUID, WITH ETHER LIKE ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
CONTAMINATION WITH CAUTION

STIC SODA, CAUSTIC POTASH OR OXIDIZING MATERIAL
MAY FORM SHOCK SENSITIVE EXPLOSIVES.

Stability Condition to Avoid: OPEN FLAMES, HOT GLOWING SURFACES OR
ELECTRIC ARCS.

Hazardous Decomposition Products: MAY EMIT HCL AND/OR PHOSGENE GAS WHEN
INVOLVED IN BURNING

===== Disposal Considerations =====

Waste Disposal Methods: CONTACT YOUR LOCAL ENVIRONMENTAL OFFICER.
MANUFACTURER RECOMENDS DISPOSAL IN A PERMITTED HAZARDOUS WASTE
MANAGEMENT FACILITY. COMP
LY WITH ALL APPLICABLE FEDERAL, STATE AND
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility fo
r the suitability of this information to their
particular situation.