

AMERON INDUSTRIAL COATINGS DIVISION -- WHITE,37875;743-720;ENAMEL LUSTERLESS --
8010-00-117-8431

=====
===== Product Identification =====

Product ID:WHITE,37875;743-720;ENAMEL LUSTERLESS

MSDS Date:01/01/1987

FSC:8010

NIIN:00-117-8431

MSDS Number: BCZQH

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

Info Phone

Num:714-529-4597

Emergency Phone Num:714-529-4597

CAGE:09869

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

=====
===== Composition/Information on Ingredients =====

Ingred Name:ETHYL BENZENE (SARA III)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 1.32%

OSHA PEL:100 PPM/125 STEL

ACGIH TLV:100 PPM/125STEL 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1

000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 32.2%

OSHA PEL:100 PPM

Ingred Name:ISOBUTYL ALCOHOL (SARA III)

CAS:78-83-1

RTECS #:NP9625000

Fraction by Wt: 6.24%

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS:111-15-9

RTECS #:KK8225000

Fraction by Wt: 0.48%

OSHA PEL:S,100 PPM

ACGIH TLV:S, 5 PPM; 9192

Ingred Name:ETHYL ACETATE (SARA
III)

CAS:141-78-6

RTECS #:AH5425000

Fraction by Wt: 3.0%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:INH:ANESTHETIC, IRRIT OF RESP TRACT OR ACUTE
CNS DEPRSSN W/HDACHE,DIZ,UNCON,COMA. SKIN & EYE: IRRIT

=====
===== First Aid Measures =====

First Aid:IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE
REMOVING CONT

AMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR.
CALL A PHYSICIAN IF SYMPTOMS PERSIST.

=====
Fire Fighting Measures
=====

Flash Point:24F TCC
Lower Limits:0.9
Extinguishing Media:SM FIRES:CO*2, DRY CHEM. LG FIRES:POLYMER FOAM
PREFERRED
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESSURE BUILD-UP

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAME, HOT
SURFACES, & ELECTRICAL,STATIC, OR FRICTIONAL SPARKS).AVOID
BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT &
NON-SPARKING TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LG QTY
IN BLDG DESIGNED TO STORE NFPA CLASS ONE FLAM LIQ. DO NOT TAKE
INTERNALY.ADD LABEL WARNING.
Other Precautions:G
ROUND CONTAINERS WHEN POURING.AVOID FREE FALL OF LIQ
IN EXCESS OF FEW IN. DO NOT FLAME CUT,BRAZE OR WELD COATED MATERIAL
W/O APPROVED RESPIRATOR OR APPROPRIATE VENTILATION. DOT:FLAM LIQUID

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:RESTRICT VENT:CHEM-MECH FLTR.CLSD:AIR-LINE TYPE
Ventilation:GEN DILTN/LOCAL EXHST TO KEEP TLV/LEL BELOW LIMIT, REMV FUM
Protective Gloves:YES
Eye Protection:YES FOR SPLASH
Other Protective Equipment:AVOID LONG
EXPOSURE TO CONTAM CLOTHING
Supplemental Safety and Health
VAPOR DENSITY:HEAVIER THAN AIR;WT PER GALLON:9.9 LBS. THIS ENAMEL IS A
QUICK DRYING, STYRENATED ALKYD TYPE.

=====
Physical/Chemical Properties
=====

HCC:F2
Boiling Pt:B.P. Text:148-290F
Vapor Pres:18
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:65.7

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
Stability

Condition to Avoid:AVOID FIRES, HEAT & HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS.DISPOSE IN ACCORDANCE W/FED, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.