

DOW CORNING CORP. -- 9-2023 PRIMER -- 8040-00-139-3708

===== Product Identification =====

Product ID:9-2023 PRIMER

MSDS Date:01/01/1985

FSC:8040

NIIN:00-139-3708

MSDS Number: BDBKZ

=== Responsible Party ===

Company Name:DOW CORNING CORP.

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-5900

Emergency Phone Num:517-496-5900

CAGE:5D028

=== Co

ntractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

===== Composition/Information on Ingredients =====

Ingred Name:N-HEPTANE

CAS:142-82-5

RTECS #:MI7700000

Fraction by Wt: 80%

OSHA PEL:500 PPM/500 STEL

ACGIH TLV:400

PPM/500STEL;9293

Ingred Name:SILICONE ADHESIVE MATERIAL, TYPE NOT SPECIFIED.

Fraction by Wt: 20%

=====  
Hazards Identification  
=====

Effects of Overexposure:IRRITATES SKIN/EYES.MAY CAUSE SLIGHT ANESTHESIA,HEADACHES,ETC.

=====  
First Aid Measures  
=====

First Aid:SKIN/EYES:FLUSH W/WATER. INHAL: REMOVE TO FRESH AIR.OBTAIN MEDICAL ATTENTION.

=====  
Fire Fighting Measures  
=====

Flash  
Point:25F,-4C,CC  
Lower Limits:1.2  
Upper Limits:6.7  
Extinguishing Media:CO\*2 OR FOAM  
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APP.& PROTECTIVE CLOTHING.  
Unusual Fire/Explosion Hazard:NONE KNOWN

=====  
Accidental Release Measures  
=====

Spill Release Procedures:USE ABSORBENT MATL.TO COLLECT & CONT.FOR SALVAGE/DISPOSAL.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:SINCE PRODUCT IS FLAMMABLE,REASONABLE CARE SHOULD BE TAKEN.STORE IN COOL,DRY & VENTILATED AREA.  
Other Precautions:NONE KNOWN

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:ORGANIC VAPOR TYPE  
Ventilation:LOCAL EXHAUST & MECHANICAL(GEN)  
Protective Gloves:RUBBER/PLASTIC  
Eye Protection:SAFETY GLASSES.  
Other Protective Equipment:AS REQD.BY LOCAL AUTHORITIES.  
Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:F2  
Boiling Pt:B.

P. Text:205F,96C

Vapor Pres:45.

Vapor Density:>1.0

Spec Gravity:0.71

Evaporation Rate & Reference: