

PARR,INC. SUB OF KOPPERS CO. -- PLASTILUBE MOLY 3 -- 9150-00-141-4481

=====
Product Identification
=====

Product ID:PLASTILUBE MOLY 3

MSDS Date:01/01/1987

FSC:9150

NIIN:00-141-4481

MSDS Number: BDBPG

=== Responsible Party ===

Company Name:PARR,INC. SUB OF KOPPERS CO.

Address:5151 DENNISON AVENUE

City:CLEVELAND

State:OH

ZIP:44101

Country:US

Info Phone Num:216-651-2010

Emergency Phone Num:216-651-2

010

CAGE:77163

=== Contractor Identification ===

Company Name:PARR,INC. SUB OF KOPPERS CO.

Address:5151 DENNISON AVENUE

Box:City:CLEVELAND

State:OH

ZIP:44101

Country:US

Phone:216-651-2010

CAGE:77163

Company Name:THIEM CORP SUB OF KOPPERS CO INC

Address:5151 DENISON AVE

Box:93019

City:CLEVELAND

State:OH

ZIP:44101-5019

Country:US

Phone:216-651-2010

CAGE:70904

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-9

5-1
RTECS #:PY8030000
Fraction by Wt: UNK
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:MOLYBDENUM DISULFIDE
CAS:1317-33-5
RTECS #:QA4697000
Fraction by Wt: UNK
OSHA PEL:10 MG/M3 TDUST (MO)
ACGIH TLV:10 MG/M3 (MO); 8990

Ingred Name:ORGANOPHYLLIC THICKENING AGENT (CLAY)
Fraction by Wt: UNK

=====
Hazards Identification
=====

Effects of Overexposure:MFR. STATES: " NIL OR NONE"

=====
First Aid Measures
=====

First Aid:WASH SKIN THOROUGHLY AFTER PROLONGED & REPEATED CONTACT
W/SKIN; EYE CONTACT: FLOOD W/ WATER; INGESTION: CONSULT PHYSICIAN

=====
Fire Fighting Measures
=====

Flash Point:>400F/>203.4CTOC
Extinguishing Media:LIKE AY OIL,CARBON DIOXIDE IS BEST
Fire Fighting Procedures:NONE -CARBON DIOXIDE IS BEST; TREAT AS CLASS
"B" FIRE
Unusual Fire/Explosion Hazard:MFR STATES: "NONE"

=====
Accidental Release Measures
=====

Spill R
Release Procedures:COLLECT SPILLED MATERIAL. RINSE FLOOR W/
APPROPRIATE & APPROVED DEGREASING SOLVENT, ABSORB UNTO INERT
MATERIAL. WASH FLOOR DOWN W/ WARM SOAPY WATER. PUT MATERIAL INTO
CONTAINERS SUITABLE FOR SHIPMENT TO DISPOSAL AREA.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. AVOID
EXCESSIVE HEAT(500F) & OPEN FLAME.
Other Precautions:NONE

=====
Exposure Controls/Personal Protection =

=====

Respiratory Protection:MFR STATES: "NONE"
Ventilation:AS REQUIRED TO MAINTAIN CONC. BELOW THE SUGGESTED TLV
Protective Gloves:OIL-PROOF TYPE
Eye Protection:PROTECTIVE GOGGLES
Other Protective Equipment:AS REQUIRED FOR TASK E HAND
Supplemental Safety and Health
COMPANY HAS PASSED THROUGH SEVERAL OWNERS AND IS CURRENTLY (DEC92)
OWNED BY KOPPERS. SEE CAGES 02307, 70904, AND 77163.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:>5
00F/>260C
Spec Gravity:0.90
Solubility in Water:NIL
Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZERS & CORROSIVES
Stability Condition to Avoid:TEMPERATURES OVER 500F & OPEN FLAMES.
Hazardous Decomposition Products:CO*2, CO, OXIDES OF SULFUR &
MOLYBDENUM
Conditions to Avoid Polymerization:WILL NOT POLYMERIZE

===== Disposal Considerations =====

Waste Disposal Methods:PUT CONTAMINED MATERIAL IN CONTAINERS SUITABLE
FOR SHIPMENT TO DISPOSAL AREA. INCINERATE OR LAND FILL IAW
APPROPRIATE FEDERAL,STATE & LOCAL REGULATIONS; DONOT INCINERATE IN
CLOSED OR SEALED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate

and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.