

KOPPERS CO.INC, 646 OWENBY DR.MARIETTA GA. 30060 -- PIGMENTED COMPONENT (SEE SUPP DATA) -- 8010-00-142-9279

===== Product Identification =====

Product ID:PIGMENTED COMPONENT (SEE SUPP DATA)

MSDS Date:01/01/1987

FSC:8010

NIIN:00-142-9279

MSDS Number: BDBSS

=== Responsible Party ===

Company Name:KOPPERS CO.INC, 646 OWENBY DR.MARIETTA GA. 30060

Emergency Phone Num:404-422-6410

CAGE:KO020

=== Contrac

tor Identification ===

Company Name:KOP-COAT INC

Address:436 7TH AVENUE

City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

Phone:800-553-5631, CHEMTREC 800-424-9300

CAGE:00297

Company Name:KOPPERS CO.INC, 646 OWENBY DR. MARIETTA GA. 30060

CAGE:KO020

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:SEC-BUTYL AC

ETATE (SARA III)

CAS:105-46-4

RTECS #:AF7380000

OSHA PEL:200 PPM

ACGIH TLV:200 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

OSHA PEL:100 PPM

THA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

=====
===== Hazards Identification =====

Effects of Overexposure:INHALATION: DIZZINESS

=====
===== First Aid Measures =====

First Aid:REMOVE FROM SOURCE, OXYGEN IF NECESSARY.

=====
===== Fire Fighting Measures =====

Flash Point:45F TCC

Lower Limits:1.0

Upper Limits:5.7

Extinguishing Media:CO2 OR DRY CHEMICAL

=====

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ANY SOURCE OF IGNITION AND FLUSH WITH WATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN CLOSED CONTAINERS AWAY FROM HEAT OR OPEN FLAME.

=====
===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST, USE OUTDOORS

Supplemental Safety and Health

ONE PART OF TWO PART SYSTEM, SEE SAME NSN P/N CONVERTER.

STRONTIUM

CHROMATE 20%, TITANIUM DIOXIDE 3.8%.

=====
===== Physical/Chemical Properties =====

Spec Gravity:1.30

Appearance and Odor:YELLOW VISCOUS LIQUID WITH KETONE ODOR

Percent Volatiles by Volume:61.0

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.