

FLEET SUPPLIES INC. -- UNLEADED GAS -- 9130-00-148-7103

===== Product Identification =====

Product ID:UNLEADED GAS

MSDS Date:03/15/1987

FSC:9130

NIIN:00-148-7103

MSDS Number: BDCLR

=== Responsible Party ===

Company Name:FLEET SUPPLIES INC.

Address:250 MAHONING AVE

Box:83831

City:CLEVELAND

State:OH

ZIP:44101

Country:US

Info Phone Num:216-621-5250

Emergency Phone Num:216-621-5250

Preparer's Name:EV

ALYN CHUTAS

CAGE:3M868

=== Contractor Identification ===

Company Name:FLEET SUPPLIES INC

Address:250 MANONING AVE

Box:City:CLEVELAND

State:OH

ZIP:44113

Country:US

Phone:216-621-5250

CAGE:3M868

===== Composition/Information on Ingredients =====

Ingred Name:GASOLINE

CAS:8006-61-9

RTECS #:LX3300000

Fraction by Wt: >95.0%

OSHA PEL:300 PPM/500 STEL

ACGIH TLV:300 PPM/500STEL;9192

Ingred Name:BENZENE (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Fraction by Wt: 0-5%

OSHA PEL:1PPM/5STEL

;1910.1028  
ACGIH TLV:10 PPM; A2; 9192  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:ACUTE:SEVERE IRRITATION OF  
EYES,TEARING OR BLURRED VISION;IRRITATION OR DRYING OF  
SKIN;INHALATION MAY CAUSE IRRITATION OF RESPIRATORY  
TRACT,HEADACHE,DIZZINESS,UNCONSCIOUS,EVEN DEATH POSSIBLE.(IN  
GEST)  
CHRONIC:DERMATITIS.  
Explanation of Carcinogenicity:CONTAINS BENZENE 0-5%;A SUSPECTED HUMAN  
CARCINOGEN (NTP,IARC & OSHA).USE EXTRA PRECAUTIONS;DO NOT INHALE.  
Effects of Overexposure:SEE HEALTH HAZARDS DATA.  
Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE  
WORSEN.

=====  
===== First Aid Measures =====

First Aid:EYES & SKIN:FLUSH WITH PLENTY OF WATER FOR ABOUT 15  
MINUTES;CALL A PHYSICIAN IF NEEDED. INHALATION:REMOVE TO FRESH  
AIR,CALL A PHYSICIAN IF NEEDED. INGESTION:DO NOT INDUCE  
VOMITING;CONSULT A PHYSICIAN IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:-35F/-37C  
Lower Limits:1.4  
Upper Limits:7.6  
Extinguishing Media:FOAM,CO\*2,DRY CHEMICAL  
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED  
AREA.  
Unusual Fire/Explosion Hazard:MATERIAL IS HIGHLY VOLATILE,VAPORS MAY  
TRAVEL ALONG THE GROUND.

=====  
===== Ac

cidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;ELIMINATE ALL IGNITION SOURCES;CONTAIN FREE LIQUID;USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.EVACUATE ALL NON-ESSENTIAL PERSONNEL FROM THE AR EA.

===== Handling and Storage =====

Handling and Storage Precautions:NO SMOKING IN STORAGE AREA;STORE IN COOL, DRY AND WELL VENTILATED AREA.KEEP AWAY FROM HEAT, OPEN FLAMES AND SPARKS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE TLV/PEL OR SCBA IN AN ENCLOSED AREA.

Ventilation:LOCAL EXHAUST TO MAINTAIN TLV/PEL

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING,EYE-WASH FOUNTAIN,SAFETY SHOWER

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN.DO NOT BREATHE VAPORS/MIST.DO NOT SMOKE,EAT OR DRINK IN WORK AREA.

Supplemental Safety and Health

FLEET SUPPLIES IS A DISTRIBUTER SUPPLYING GASOLINE FROM A NUMBER OF REFINERS,BUT SUPPLING THEIR OWN MSDS.

===== Physical/Chemical Properties =====

HCC:F1

Boiling Pt:B.P. Text:55F/13C

Vapor Pres:760 MMHG

Vapor Density:1.2

Spec Gravity:0.75

Evaporation Rate & Reference: