

LUBRICATING SPECIALITIES CO, TECHNOLUBE PROD DIV -- A3000, MIL-H-83282C HYD FLUID --  
9150-00-149-7432

===== Product Identification =====

Product ID:A3000, MIL-H-83282C HYD FLUID

MSDS Date:04/27/1993

FSC:9150

NIIN:00-149-7432

MSDS Number: BDCPL

=== Responsible Party ===

Company Name:LUBRICATING SPECIALITIES CO, TECHNOLUBE PROD DIV

Address:8015 PARAMOUNT BLVD

City:PICO RIVERA

State:CA

ZIP:90660-488

8

Country:US

Info Phone Num:310-928-3311, FAX 310-928-1428

Emergency Phone Num:310-928-3311, CHEMTREC 800-424-9300

Preparer's Name:RICHARD J.EBERHARDT

CAGE:2X769

=== Contractor Identification ===

Company Name:LUBRICATING SPECIALTIES CO. TECHNOLUBE PRODUCTS DIV

Address:3365 E. SLAUSON AVE

Box:City:LOS ANGELES

State:CA

ZIP:90058

Country:US

Phone:562-776-4033; FAX:562-776-4003

CAGE:8Y842

Company Name:NAUGHTON ENERGY CORP

Address:RT 940

Box:709

City:POCONO PINES

State:PA

ZIP:18350-0709

Country:US

Ph

one:570-646-0422  
CAGE:1DL10  
Company Name:TECHNOLUBE PRODUCT COMPANY  
Address:8015 PARAMOUNT BLVD.  
Box:City:PICO RIVERA  
State:CA  
ZIP:90660-4811  
Country:US  
Phone:562 776-4000 GEN: 562-776-4000  
CAGE:2X769

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SYNTHETIC HYDROCARBON BASE OIL  
CAS:68649-12-7  
Fraction by Wt: 200C  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.  
Fire Fighting Procedures:DO NOT ENTER ANY ENCLOSED OR CONFINED AREA  
  
WITHOUT PROPER PROTECTIVE EQUIPMENT AND SELF CONTAINED BREATHING  
APPARATUS.  
Unusual Fire/Explosion Hazard:SLIGHTLY COMBUSTIBLE. WHEN HEATED ABOVE  
FLASH POINT, WILL RELEASE FLAMMABLE VAPORS WHICH CAN BURN IN OPEN  
OR BE EXPLOSIVE IN CONFINED SPACES IF IGNITED.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:STOP FLOW. WIPE OR MOP UP OR ABSORB WITH  
DIATOMACEOUS EARTH OR OTHER INERT MATERIAL. STORE IN APPROPRIATE  
CONTAINER FOR DISPO  
SAL.  
Neutralizing Agent:NOT APPLICABLE.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL-VENTILATED  
PLACE. KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP AWAY FROM  
HEAT, SPARKS, FLAMES AND INCOMPATIBLE MATERIALS.  
Other Precautions:WASH OR TAKE SHOWER IF GENERAL CONTACT OCCURS. REMOVE  
OIL-SOAKED CLOTHING AND LAUNDRER BEFORE REUSE. DISCARD CONTAMINATED  
LEATHER GLOVES AND SHOES.

=====  
Exposure Controls/  
=====

Personal Protection =====

Respiratory Protection:NOT NEEDED IN NORMAL SERVICE.

Ventilation:USE GENERAL DILUTION VENTILATION.

Protective Gloves:CHEMICALLY RESISTANT GLOVES

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:CHEMICALLY RESISTANT BOOTS AND APRONS  
RECOMMENDED.PROVIDE A LOCAL EYE WASH STATION AND QUICK DRENCH  
SHOWER.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET  
CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF TH  
E WORK  
AREA.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>599F,>315C

Vapor Pres:1.0

Spec Gravity:0.853

Evaporation Rate & Reference: