

ESSEX CHEM CORP, SPECIALTY CHEM DIV -- PRO-SEAL 890 BASE, CLASS C -- 8030-00-152-0012

=====  
Product Identification  
=====

Product ID:PRO-SEAL 890 BASE, CLASS C

MSDS Date:01/01/1985

FSC:8030

NIIN:00-152-0012

MSDS Number: BDCSL

=== Responsible Party ===

Company Name:ESSEX CHEM CORP, SPECIALTY CHEM DIV

Address:19451 SUSANA RD

City:COMPTON

State:CA

ZIP:90221-5713

Country:US

CAGE:KO319

=== Contractor I

dentification ===

Company Name:ESSEX CHEM CORP, SPECIALTY CHEM DIV

Address:19451 SUSANA RD

Box:City:COMPTON

State:CA

ZIP:90221-5713

Country:US

CAGE:KO319

Company Name:ESSEX CHEMICAL CORP PRO-SEAL DIV

Address:19451 SUSANA RD

Box:City:COMPTON

State:CA

ZIP:90221-5713

Country:US

Phone:310-537-7600

CAGE:83527

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 5-7%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50

PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:MAY CAUSE SKIN/EYE IRRIT

===== First Aid Measures =====

First Aid:WASH HANDS THOROUGHLY AFTER USE, FLUSH EYES W/WATER  
COPIOUSLY. INGEST: GIVE EMETIC & CONSULT MD.

===== Fire Fighting Measures =====

Flash Point:66F CC  
Lower Limits:1.3  
Upper Limits:7.0  
Extinguishing Media:CO  
\*2, FOAM, DRY CHEM  
Fire Fighting Procedures:WATER NOT REC  
Unusual Fire/Explosion Hazard:VOLATILE SLVNT

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP SPILLAGE W/SWEEPING CMPD &/OR RAGS &  
SLVNT, MFR REC

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN CLOSED CNTNR AT 80F OR BELOW.  
AVOID OPEN FLAMES & ELECTRICAL SPARKS WHEN USING.  
Other Precautions:RED LABEL MATL

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE W/ADEQUATE VENT  
Ventilation:YES  
Protective Gloves:BUNA N-GLOVES  
Eye Protection:FACE SHLDS/GOGGLES  
Other Protective Equipment:COVERALL/APRON  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3  
Boiling Pt:B.P. Text:110.7C  
Vapor Pres:37  
Vapor Density:3.1  
Spec Gravity:0.86  
Evaporation Rate & Reference:4.5 ETHYL ETHER  
Solubility in Water:NEGLIGIBLE  
Appea

rance and Odor:WHITE PASTE, ORGANIC SULFIDE ODOR  
Percent Volatiles by Volume:15.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:PREFERABLY BY BURNING, MFR REC

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of Ame  
rica in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.