View NSN Online: https://aerobasegroup.com/nsn/8030-00-155-6444

Product ID:FEL-PRO C5-A MSDS Date:01/01/1985 FSC:8030 NIIN:00-155-6444 **MSDS Number: BDCXT** === Responsible Party === Company Name: FEL-PRO, INC Emergency Phone Num:312-761-4500 CAGE: JO924 === Contractor Identification === Company Name: FEL-PRO INC DIV OF FELT PRODUCTS MFG CO Address:7450 N MCCORMICK Box:1103 City:SKO KIE State:IL ZIP:60076-4046 Country:US Phone:847-674-7700 OR 312-761-4500 CAGE:73165 Company Name: FEL-PRO, INC CAGE: JO924

Ingred Name:COPPER (SARA III) CAS:7440-50-8 RTECS #:GL5325000 OSHA PEL:0.1MG/M3 FUME/1 DUST ACGIH TLV:0.2MG/M3 FUME; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:GRAPHITE (UNKNOWN PERCENT) RTECS #:VV7780000

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT) CAS:8002-05-9 RTECS #

:SE7449000 OSHA PEL:400 PPM ACGIH TLV:400 PPM; 8990

======================================
Effects of Overexposure: AVOID EYE CONTACT. AVOID INGESTION.
======================================
First Aid:INGESTION: CALL MD IMMEDIATELY. EYE: IMMEDIATELY FLUSH W/WATER AT LEAST 15 MIN. CALL MD. SKIN: WASH W/MILD SOAP AND WATER.
======================================
Flash Point:ASTM D92-57 31OF Extinguis hing Media:CO*2, DRY CHEMICALS Fire Fighting Procedures:SAME AS FOR PETROLEUM GREASE FIRES Unusual Fire/Explosion Hazard:NONE
======================================
Spill Release Procedures:WIPE UP W/RAGS - SHOVEL, SCRAPE - FINISH CLEANING W/DETERGENT & WATER OR HIGH FLASH POINT CLEANER W/VENTILATION. (MFG REC)
======================================
Handling and Storage Precautions:NORMAL STORAGE AND HANDLING. MAINTAIN GOO D PERSONAL HYGIENE.
======== Exposure Controls/Personal Protection ====================================
Protective Gloves:NOT NEEDED Eye Protection:RECOMMENDED, BUT NOT NEED Supplemental Safety and Health MFG LISTS VAPOR PRESS, EVAP RATE, % VOLATILE BY VOLUME TO BE NIL
======================================
HCC:N1 Boiling Pt:B.P. Text:400 F Spec Gravity:1.2 Solubility in Water:NEGLIGIBLE Appearance and Odor:COPPER COLORED PASTE - SLIGHT PETROLEUM ODOR

====== Stabil

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS, CHEMICALLY UNSTABLE COMPOUNDS Hazardous Decomposition Products:NONE

Waste Disposal Methods:NORMAL FOR GREASE PRODUCTS. IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of De

fense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.