

EVERSEAL MFG CO INC -- TT-F-336, WOOD FILLER -- 8010-00-160-6897

===== Product Identification =====

Product ID:TT-F-336, WOOD FILLER

MSDS Date:01/01/1985

FSC:8010

NIIN:00-160-6897

MSDS Number: BDDJD

=== Responsible Party ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

City:RIDGFIELD

State:NJ

ZIP:07657-2329

Country:US

Info Phone Num:201-943-4986 / FAX 201-943-1123

Emergency Phone Num:2

01-943-4986

CAGE:72988

=== Contractor Identification ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

Box:City:RIDGFIELD

State:NJ

ZIP:07657-2329

Country:US

Phone:201-943-4986

CAGE:72988

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 16%

OSHA PEL:100 PPM

Ingred Name:LEAD DRIER (OSHA PEL FROM 29CFR 1910.1025)

Fraction by Wt: 0.5%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0

.15 MG/M3 (PB);8990

=====
Hazards Identification
=====

Effects of Overexposure:DRYING OF SKIN. EYE IRRITATION. EXCESSIVE
INHAL-ANESTHESIA, HEADACHE, DIZZ, NAUSEA, UPPER RESP. IRR

=====
First Aid Measures
=====

First Aid:INHAL:MOVE TO FRESH AIR. APPLY ART. RESP. IF NEC. CALL MD.
SKIN:WASH W/MILD SOAP & WATER. APPLY A MILD CREAM. IN SEVERE
CASE-CALL MD. INGEST:CALL MD. EYE:IMMEDIATELY FLUSH W/WATER AT
LEAS
T 15 MIN. CAL L MD.

=====
Fire Fighting Measures
=====

Flash Point:105 F TAG
Lower Limits:0.9
Upper Limits:6.0
Extinguishing Media:EXCLUDE AIR-USE FOAM, CO*2, STEAM, DRY CHEMICAL
Fire Fighting Procedures:DO NOT USE WATER EXCEPT FOR COOLING AFFECT
Unusual Fire/Explosion Hazard:USE SELF-CONTAINED BREATING APPARATUS

=====
Accidental Release Measures
=====

Spill Release Procedures:FLUSH W/WATER INTO RETAINING AREA OR
CONTAINER. AVO
ID SPARKS, FIRE, OR HOT METAL SURFACES. SMALL
QUANTITIES MAY BE ABSORBED ONTO AN APPROPRIATE ABSRBANT

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP COOL & AWAY FROM SOURCES OF
IGNITION. PROVIDE ADEQUATE VENTILATION. AVOID PROLONGED / REPEATED
CONTACT.
Other Precautions:DOT CLASSIFICATION: COMBUSTIBLE

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:IF TLV EXCEEDED USE CARTRIDGE R

ESPIRATOR OR
MASK.

Ventilation:ADEQUATE TO KEEP CONCENTRATION BELOW TLV & FLAMMABLE LIMITS

Protective Gloves:IMPERMEABLE

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:APRON, BARRIER CREAM

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:326 TO 387F

Vapor Pres:5

Vapor Density:4.9

Spec Gravity:1.68

Evaporation Rate & Reference:0.1 N-BUTYL ACET.

Solubility in Water:NEGLIGIBLE

Appearance and Odor:ST

ANDARD PAINT ODOR

Percent Volatiles by Volume:35

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME, FIRE

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CO &
CO*2.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE UNDER SAFE CONDITIONS OR DISPOSE IN
ACCORDANCE W/APPLICABLE LOCAL,
STATE & FEDERAL CODES. (MFG REC)

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this infor

mation to their
particular situation.