

SCM CORP. (COATINGS AND RESINS DIV.) -- SOLVENT-907-S-2103 A -- 8010-00-162-5289

=====  
Product Identification  
=====

Product ID: SOLVENT-907-S-2103 A

MSDS Date: 01/01/1985

FSC: 8010

NIIN: 00-162-5289

MSDS Number: BDDQB

=== Responsible Party ===

Company Name: SCM CORP. (COATINGS AND RESINS DIV.)

Address: 925 EUCLID AVE

City: CLEVELAND

State: OH

ZIP: 44115

Country: US

CAGE: KO372

=== Contractor Identification

===

Company Name: GLIDDEN CO MEMBER OF ICI WORLD PAINTS

Address: 925 EUCLID AVE

Box: 15049

City: CLEVELAND

State: OH

ZIP: 44115

Country: US

Phone: 216-344-8000

CAGE: 72818

Company Name: SCM CORP. (COATINGS AND RESINS DIV.)

Address: 925 EUCLID AVE

Box: City: CLEVELAND

State: OH

ZIP: 44115

Country: US

CAGE: KO372

=====  
Composition/Information on Ingredients  
=====

Ingred Name: N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS #: EO1400000

Fraction by Wt: 25.0%

OSHA PEL: 100 PPM

ACGIH TLV: S, C 50 PPM; 9

293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)  
CAS:8030-30-6  
RTECS #:DE3030000  
Fraction by Wt: 25.0%  
OSHA PEL:100 PPM

Ingred Name:N-BUTYL ACETATE (SARA III)  
CAS:123-86-4  
RTECS #:AF7350000  
Fraction by Wt: 40.0%  
OSHA PEL:150 PPM/200 STEL  
ACGIH TLV:150 PPM/200STEL;9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:N-AMYL ACETATE (SARA III)  
CAS:628-63-7  
RTECS #:AJ1925000  
Fraction by Wt: 10.0%  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM; 9192  
EPA Rp  
t Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:POSS. DERMATITIS; IRRITATION OF EYES, SKIN &  
RESP. TRACT; HEADACHE, DIZZINESS, UNCONSCIOUSNESS, COMA

===== First Aid Measures =====

First Aid:FUMES: REMOVE VICTIM TO FRESH AIR, RESTORE BREATHING IF  
NECESSARY, GET MEDICAL ATTENTION; EYES: FLUSH WELL WITH WATER; CALL  
PHYSICIAN. SKIN: WASH WELL WITH SOAP AND WATER.

==

=====  
Fire Fighting Measures  
=====

Flash Point:76F TCC

Lower Limits:01.0

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WATER SPRAY MAY BE USED TO COOL CLOSED CANS TO  
AVOID EXPLOS.

Unusual Fire/Explosion Hazard:AVOID HEAT, SPARKS, FLAME AND HOT  
SURFACES. CLOSED CANS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL IGNITION

SOURCES.MOP SPILLS WITH

INERT ABSORBENT.VENTILATE AREA.BURN SWEEPINGS IN A SAFE AREA.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE BELOW 100F. KEEP CONTAINERS  
CLOSED & AWAY FROM HEAT AND OPEN FLAME.

Other Precautions:AVOID PROLONGED SKIN CONTACT, BREATHING VAPORS OR  
SPRAY MIST. DO NOT TAKE INTERNALLY.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:CONFINED AREAS-AIRLINE;RESTR  
ICTED VENT.-SPRAY

MASK W/ORGANIC VAPOR F

Ventilation:DILUTION OR LOCAL EXHAUST TO KEEP BELOW TLV.

Protective Gloves:SOLVENT RESIST.

Eye Protection:SPLASH-PROOF GOGGLES

Supplemental Safety and Health

MIL-T-6095 B THINNER-COMPOSITION G; VAPORS ARE HEAVIER THAN AIR.

=====  
Physical/Chemical Properties  
=====

HCC:F4

Boiling Pt:B.P. Text:243 TO 400F

Vapor Pres:8

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:100.

=====  
Stab  
=====

ility and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: OVOID CONTAMINATION WITH FOREIGN MATERIALS.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.