

HOBART BROTHERS COMPANY -- LH-1118 -- 3439-00-165-4165

=====
Product Identification
=====

Product ID:LH-1118
MSDS Date:01/01/1987
FSC:3439

NIIN:00-165-4165
MSDS Number: BDDST

=== Responsible Party ===

Company Name:HOBART BROTHERS COMPANY
Emergency Phone Num:(513) 339-6011
CAGE:28835

=== Contractor Identification ===

Company Name:HOBART BROTHERS CO
Address:600 W MAIN ST HOBART SQUARE
Box:City:TROY

State:OH
ZIP:45373
Country:US
Phone:513-339-6000
CAGE:28835

=====
Composition/Information on Ingredients
=====

Ingred Name:CALCIUM FLUORIDE
CAS:7789-75-5
RTECS #:EW1760000
Fraction by Wt: 6.0%
OSHA PEL:2.5 MG/M3 (F)
ACGIH TLV:2.5 MG/M3 (F); 8990

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 3.0%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:FERRO MANGANESE(USED IN FLUX)
Fraction by Wt: 1.0%

Ingred Name:FERRO SILICON(A P

ART OF FLUX)
Fraction by Wt: 2.0%

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)
CAS:1317-65-3
RTECS #:EV9580000
Fraction by Wt: 6.0%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9192

=====
Hazards Identification
=====

Effects of Overexposure:SKIN:NOT KNOWN;INHAL:FUMES DURING WELDING MAY CAUSE FAINTNESS,NAUSEA,ETC.

=====
First Aid Measures
=====

First Aid:USE STANDARD FIRST AIR PROCEDURES. CALL EMERGENCY MEDICAL CARE.

=====
Fire Fighting Measures
=====

Flash Point:NONE
Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR.
Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

=====
Accidental Release Measures
=====

Spill Release Procedures:USE WORK GLOVES.IF STOCK SPILLED OUT OF BOX/CAN,COLLECT & REUSE.IF ROD IS BROKEN TO SMALL PIECES & CANNOT BE REUSED,SEND FOR RECLAMATION PROCESS. KEEP WASTE IN COVERED CONTAINERS WHEN CANNOT BE RECLAIMED.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED
Other Precautions:ARC/SPARKS COULD BE SOURCE OF IGNITION OF COMBUSTIBLE PRODUCTS.

=====
Exposure Controls/Personal Protection
=====

ction =====

Respiratory Protection:WELD FUME RESP OR AIRLINE RESP FOR CONFINED SPACES

Ventilation:LOCAL EXHAUST FOR CONFINED AREA;MECH(GEN):WHEN TLV EXCEEDS.

Protective Gloves:WELDERS GLOVES

Eye Protection:COLORED ADSORPTV LENS#9

Other Protective Equipment:PROTECTIVE CLOTHING SUCH AS LEATHER APRON.

Supplemental Safety and Health

MSDS NOT DATED; COMPONENTS CONTD:NIOSH-6:IRON, 6%; NIOSH-7:NICKEL-1%; NIOSH-8:FERRO MOLYBDENUM-0.5%; NIOSH-9:POTASSIUM SILICATE:3%

=====

Physical/Chemical Properties =====

HCC:N1

Solubility in Water:NEGLIGIBLE

Appearance and Odor:STEEL CORE WIRE COATED W/FLUX.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NOT KNOWN

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:NOT KNOWN

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FUL

L COMPLIANCE WITH ALL APPLICABLE

INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and as

some responsibility for the suitability of this information to their particular situation.