View NSN Online: https://aerobasegroup.com/nsn/8010-00-171-1509

PRATT AND LAMBERT INC -- 786702 LACQUER C/N GLOSS BLACK 17038 -- 8010-00-171-1509

Product ID:786702 LACQUER C/N GLOSS BLACK 17038

MSDS Date:01/01/1985

FSC:8010

NIIN:00-171-1509

MSDS Number: BDFJK === Responsible Party ===

Company Name: PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153 City:WICHITA

State:KS ZIP:67201 Country:US

Info Phone Num:316-733-1361

Fme

rgency Phone Num:716-873-6000 DOT EMER 8002553924

CAGE:61196

=== Contractor Identification ===

Company Name: PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

======= Composition/Information on Ingredients ========

Ingred Name: ISOBUTYL ACETATE

RTECS #:NP9100000 Fraction by Wt: 25% ACGIH TLV:150 PPM

Ingred Name: ISOBUTYL ALCOHOL (SARA III)

CAS:78-83-1

RTECS #:NP9625000 Fraction by Wt: 8% OSHA PEL:100 PPM ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 8%

OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: NAPHTHA ALIPHATIC

Fraction by Wt: 8% ACGIH TLV:200 PPM

Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000 Fraction by Wt: 8% OSHA PEL:100 PPM

========== Hazards Identification ================

Effects of Overexpos

ure:INHAL:ANEST,IRRIT OF RESPIR TRACT OR ACUT NERV SYS DEPRESN,HDACH,DIZZ,CONFUS,UNCONSCIOUS, COMA.

First Aid:IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILEREMOVING CONTAMINATED CLOTHING. IF INHALATED, REMOVE TO FRESH AIR. CALL A PHYSCIAN IF SYMPTOMS PERSIST.

========== Fire Fighting Measures ===============

Flash Point: 13 F TCC -11 C

Extinguishing Media: USE FIRE EXTING (CO*2, DRY CH

EM OR ALCOH FOAM)LO


FIRE-POLYMER

Fire Fighting Procedures: SELF-CONTAINED BREATH APPARATUS SHLD BE AVAIL F/FIREMEN.

Unusual Fire/Explosion Hazard: KEEP CONTNRS TIGHTLY CLOS: ISOLAT FR HEAT, ELECTR EQPMT, SPARKS & OPEN FLAME. CLOS CONTNRS MAY EXPLO(SUP

======== Accidental Release Measures ===========

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES,HOT SURFACES,&ELECTRICAL, STARIC, OR FRICTIONAL SPARKS) AVOID BREATHING VAPORS.VENTILATE AREA.REMOVE



LATIONS.INCINERATE IN APPRVD FACILITY.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume res

ponsibility for the suitability of this information to their particular situation.