

AMERON INDUSTRIAL COATINGS DIVISION -- 741-606 GRAY #36118 -- 8010-00-180-5927

===== Product Identification =====

Product ID:741-606 GRAY #36118

MSDS Date:01/01/1985

FSC:8010

NIIN:00-180-5927

MSDS Number: BDFXZ

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

Info Phone Num:714-529-4597

Emergency Phone Nu

m:714-529-4597

CAGE:09869

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 37.9%

OSHA PEL:100 PPM

===== Hazards Identification =====

Effects of Overexposure:IN

HALATION:: ANESTHETIC, IRRITATION NERVOUS
SYSTEM DEPRESSION BY HEADACHES, DIZZINESS OR COMA.

===== First Aid Measures =====

First Aid:IN CASE OF CONTACT, FLUSH SKIN AND EYES WITH PLENTY OF WATER
WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH
AIR. CALL A PHYSICIAN IF SYMPTOMS PERSIST.

===== Fire Fighting Measures =====

Flash Point:86FF T.C.C

Lower Limits:1.1

Extinguishing Media:USE CARBON DI

OXIDE OR DRY CHEMICAL FOR SMALL FIRES

Fire Fighting Procedures:SELF-CONTAINED BREATHING SHOULD BE AVAILABLE
FOR FIREMEN.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESSURE BUILD-UP.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES HOT
SURFACES, AND ELECTRICAL, STATIC, OR FRICONAL SPARKS). AVOID
BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT SORBENT AN
D
NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE
QUANTITIES IN BLDGS DESIGNED AND PROTECTED FOR STORAGE OFFPA CLASS
1 FLAMMABLE (OR COMBUSTIBLE) LIQUID.

Other Precautions:DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED
WHEN POURING. DO NOT FLAME CUT, BRAZE OR WELD COATED MATERIAL W/OUT
USUREAU OF MINES APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.

=====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN CONFINED AREAS USE BUREAU OF MINES APPROVED
AIR LINE HOODS.

Ventilation:PROVIDE GENERAL DILUTION VENTILATION IN VOLUME KEEP TLV.

Protective Gloves:PROLONGED

Eye Protection:USE SAFETY EYEWEAR

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO
CONTAMINATED CLOTHING.

Supplemental Safety and Health

ENMAR P.O. BOX 2153 WICHITA, KANSAS 67201

===== Physical/Chemical Properties =====

=====

HCC:F3
Boiling Pt:B.P. Text:311-373F
Vapor Density:YES
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:59.7

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:AVOID FIRES, HEAT, AND HOT SURFACES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS. INCINE
RATE APPROVED FACILITY. DO NOT
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility fo
r the suitability of this information to their
particular situation.