

CSD, INC -- MIL-T-81772A -- 8010-00-181-8079

=====  
Product Identification  
=====

Product ID:MIL-T-81772A

MSDS Date:01/01/1987

FSC:8010

NIIN:00-181-8079

MSDS Number: BDGNY

=== Responsible Party ===

Company Name:CSD, INC

Address:5 HACKBURY ST

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Info Phone Num:409-756-1065/713-797-0395(MEDICAL)

Emergency Phone Num:713-923-6641/800-424-9300(CHEMTREC)

CAG

E:0LWP6

=== Contractor Identification ===

Company Name:CHEMICAL SPECIALISTS AND DEVELOPMENT INC

Address:2210 HACKBERRY LN

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Phone:409-756-1065

CAGE:4N760

Company Name:CSD, INC

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Phone:800-424-9300

CAGE:0LWP6

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SOLVENTS

Fraction by Wt: 100%

=====  
Hazards Identification  
=====

Effects of O

verexposure:INHAL:ANEST:IRRITATES RESPIR TRACT.MAY CAUS  
NERV SYS DEPRESS BY HDACH,DIZZ,STAGG,CONFUS OR COMA.

=====  
First Aid Measures  
=====

First Aid:EYES & SKN:FLUSH W/WATER F/AT LEAST 15 MIN.IF IRRIT GET MED  
ATTN.VAPORS:REMOV FR EXPOSURE.RESTORE BREATHING. SWALLOWING:CALL  
DR. IMMED.DO NOT INDUCE VOMITING.

=====  
Fire Fighting Measures  
=====

Flash Point:42F TCC 6C TCC

Lower Limits:1.7

Extinguishing Media:CO\*2

, DRY CHEMICAL,OR FOAM.

Fire Fighting Procedures:WATR SPRA MAY BE INEFFECT ON FIRE.CN PROTCT  
FIREFIGHTRS.

Unusual Fire/Explosion Hazard:KEEP CONTNRS TIGHTLY CLOS.KP AWAY FR  
HEAT,SPARKS,ELECT EQPMT, & OPN FLAM.CLOS CONTNR MAY EXPLODE.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOV ALL SOURCES OF IGNITION. AVOID BREATHING  
VAPOR.VENTILATE. REMOV W/INERT ABSORBENT, NON-SPARKING PRODUCTS.

=====  
Handling and Storage =  
=====

Handling and Storage Precautions:DO NOT STORE ABOV 120F.STORE LG AMTS  
IN STRUCTRES MADE F/OSHA CL 1B LIQUIDS.AVD FREE FALL OF LIQUID.CRND  
CONTNR WHN POURNG.DO NOT FLAME CUT,SAW,BRAZE.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:VENTILATE TO KP AIR BELO 65PPM.IF OVR TLV,USE  
SELF-CONTND AIR PACK.

Ventilation:LOC EXHAUST-PREFERABLE, MECH-ACCEPTABLE

Protective Gloves:RECOMMENDED

Eye Protection:CHEMICAL GOGGLES

Supple

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:304

Vapor Pres:35

Vapor Density:3.4

Spec Gravity:.886

Evaporation Rate & Reference:ETHER 16.8

Solubility in Water:APPRECIABLE

Appearance and Odor:CLEAR, WATER-WHITE, KETONE ODOR.

Percent Volatiles by Volume:106

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:HE

AT, SPARKS, & OPEN FLAME.

Hazardous Decomposition Products:CARBON MONOXIDE FROM BURNING

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE ACCORDING TO AIR POLLUTION  
REGULATIONS. DO NOT INCINERATE IN CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.