

MOBIL OIL CORPORATION -- DELVAC 1330 (SAE 30) -- 9150-00-189-6729

===== Product Identification =====

Product ID:DELVAC 1330 (SAE 30)

MSDS Date:01/01/1985

FSC:9150

NIIN:00-189-6729

MSDS Number: BDHSG

=== Responsible Party ===

Company Name:MOBIL OIL CORPORATION

Emergency Phone Num:212-883-4242

CAGE:1G112

=== Contractor Identification ===

Company Name:MOBIL CORP

Address:150 E 42ND ST

Box:City:NEW YO

RK

State:NY

ZIP:10017-5612

Country:US

Phone:212-883-4242

CAGE:57635

Company Name:MOBIL OIL CORPORATION

Address:3225 GALLOWS RD

City:FAIRFAX

State:VA

ZIP:22037-0001

Phone:(703) 846-1482

CAGE:1G112

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: >90%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:ADDITIVES

Fraction by Wt: 0.5 LITER(PINT)

INGEST, IM MED

GIVE 1-2 GLASSES OF H*20. (SEE SUPPDATA)

=====
===== Fire Fighting Measures =====

Flash Point:425F;218C (OC)
Extinguishing Media:CO*2, FOAM, DRY CHEM
Fire Fighting Procedures:USE NIOSH/MSHA APPRVD SCBA
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON FIRE RETARDANT TREATED SAWDUST,
DIATOMACEOUS EARTH, OR OTHER ABSORBENT. SHOVEL UP & REMOVE. REPORT
SPILL TO APPROPRIATE
AUTHORITIES. SPILLS THAT MAY REACH WATER(DRY
CREEKS INCLUDED)CALL COAS T GUARD 800-424-8802.

=====
===== Handling and Storage =====

Other Precautions:EYE PROTECTION:IF EYE CONTACT IS LIKELY USE CHEM TYPE
GOGGLES OR SAFETY GLASSES W/SIDE SHIELDS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NEEDED UNDER NORMAL CONDITIONS AND W/
ADEQUATE VENT(MFR)
Ventilation:ADEQUATE VENT TO KEEP BELDW TLV.
Protective
Gloves:SEE OTHER EQUIP
Eye Protection:SEE OTHER PRECAUTIONS
Other Protective Equipment:OIL IMPERVIOUS GLOVES FOR RPTD/PRLNG
EXPOSURE.
Supplemental Safety and Health
FIRST AIR PROCEDURE:INGEST-CALL MD/POISON CONTROL FOR WAY TO INDUCE
VOMIT. IF UNCON-DO NOT INDUCE VOMIT OR GIVE ANYTHING BY MOUTH.
CONTAINER SIZE:55 GAL DRUM. VP:600F;316C
Solubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR LIQUID;MILD ODOR

=====
===== Stability and Reactivity Data =====

Stabil

ity Indicator/Materials to Avoid: YES
STRONG OXIDIZERS
Stability Condition to Avoid: STRONG OXIDATION
Hazardous Decomposition Products: METAL OXIDES, CO

===== Disposal Considerations =====

Waste Disposal Methods: MFR RECOMMENDS DILUTING WASTE W/ A FLAMMABLE SOLVENT (FL PT ABOUT 100F) & DISPOSE BY SUPERVISED INCINERATION. DISPOSAL METHOD MUST BE IAW FEDERAL, STATE AND LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This

information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.