

BEETON DICKINSON & CO -- ADHESIVE LIQUID,SURGICAL/ETHYL ACOHOL -- 6510-00-200-0160

===== Product Identification =====

Product ID:ADHESIVE LIQUID,SURGICAL/ETHYL ACOHOL

MSDS Date:01/01/1985

FSC:6510

NIIN:00-200-0160

MSDS Number: BDJFM

=== Responsible Party ===

Company Name:BEETON DICKINSON & CO

Address:1 BECTON DR

City:FRANKLIN LAKES

State:NJ

ZIP:07417-1880

Country:US

Emergency Phone Num:NONE

CAGE:K

O577

=== Contractor Identification ===

Company Name:BECTON DICKINSON AND CO, BECTON DICKINSON DIV.

Address:1 BECTON DR

City:FRANKLIN LAKES

State:NJ

ZIP:07417-1884

Country:US

Phone:201-847-4000, 800-333-4831

CAGE:06531

Company Name:BEETON DICKINSON & CO

Address:1 BECTON DR

Box:City:FRANKLIN LAKES

State:NJ

ZIP:07417-1880

Country:US

CAGE:KO577

===== Composition/Information on Ingredients =====

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

OSHA PEL:1000 PPM

AC

=====  
Hazards Identification  
=====

Effects of Overexposure:IRRIGATION OF EYES & RESPIRATORY TRACT;HEADACHE,DIZZINESS,DROWSINESS,MENTAL CONFUSION,FATIGUE,NAUSEA

=====  
First Aid Measures  
=====

First Aid:IRRIGATE EYES W/WATER,STOMACH ASH,IF SWALLOWED,FOLLOWED BY SALINE CATHARSIS

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC

Flash Point:=12.2C, 53

.9F

Lower Limits:3.3

Upper Limits:19.0

Extinguishing Media:DRY CHEMICAL,FOAM,OR CARBON DIOXIDE,WATER SPRAY INEFFECTIVE.

Unusual Fire/Explosion Hazard:FLAME,FIRE,IGNITION SOURCES MAY PRODUCE EXPLOSION

=====  
Accidental Release Measures  
=====

Spill Release Procedures:NO FLARES,SMOKING OR FLAMES IN HAZARD AREA.STOP LEAK IF WITHOUT RISK.USE WATER SPRAY TO REDUCE VAPORS.LARGE SPILLS DIKE FOR LATER DISPOSAL.SMALL SPILLS:TAKE UP WITH SAND,EARTH,OR OTHER NONCOMBUSTIBLE ABSORBENT MATERIAL.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:PROTECT CONTAINERS AGAINST PHYSICAL DAMAGE.STORE AWAY FROM POSSIBLE IGNITION SOURCES.ALL PRECAUTIONS FOR THE ELIM.OF STATIC ELECTRICITY BE TAKEN.

Other Precautions:AVOID STORAGE WITH PERCHLORATES,PEROXIDES,CHROMIC ACID & NITRIC ACID.WEAR CHEMICAL GOGGLES,CHEMICAL CARTRIDGE RESPIRATOR,RUBBER GLOVES & RUBBER BOOTS.

=====  
Exposure Contr  
=====

ols/Personal Protection =====

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS OR CHEMICAL CARTRIDGE RESPIRATOR

Ventilation:AS REQUIRED TO CONTROL TLV IN AIR

Protective Gloves:RUBBER

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:RUBBER BOOTS.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:=78.5C, 173.3F

Spec Gravity:0.80

Solubility in Water:APPRECIABLE

Appearance and Odor:COLORLESS,HYGROS

COPIC,VOLATILE LIQUID,PLEASANT.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATLS,PERCHLORATES,PEOXIDES,CHROMIC ACID,HNO\*3

===== Disposal Considerations =====

Waste Disposal Methods:SPRAY INTO A FURNACE UNDER APPROVED CONTROLLED CONDITIONS.INCINERATION WILL BECOME EASIER BY MIXING WITH A MORE FLAMMABLE SOLVENT.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.