

AMERON PROTECTIVE COATINGS -- 703-200 -- 8010-00-234-5176

=====
Product Identification
=====

Product ID:703-200
MSDS Date:01/01/1987
FSC:8010
NIIN:00-234-5176
MSDS Number: BDLKD
=== Responsible Party ===
Company Name:AMERON PROTECTIVE COATINGS
Address:201 NORTH BERRY STREET
City:BREA
State:CA
ZIP:92622-1020
Country:US
Info Phone Num:714-529-1951
Emergency Phone Num:714-529-1951
CAGE:0Y2E4
=== Cont
ractor Identification ===
Company Name:AMERON PROTECTIVE COATINGS
Address:201 NORTH BERRY STREET
Box:1020
City:BREA
State:CA
ZIP:92622-1020
Country:US
Phone:714-529-1951
CAGE:0Y2E4

=====
Composition/Information on Ingredients
=====

Ingred Name:BENZIN, NAPHTHA, MINERAL SPIRITS, PETROLEUM NAPHTHA
CAS:8030-30-6
RTECS #:DE3030000
Other REC Limits:STEL 400 PPM
OSHA PEL:100 PPM
ACGIH TLV:300 PPM

=====
Hazards Identification
=====

Routes of Entry:

Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: ANESTHETIC. IRRITATION OF
RESPIRATORY TRACT. MAY CAUSE NERVOUS SYSTEM DEPRESSION. SKIN/EYES:
IRRITATION.
Effects of Overexposure:IRRITATION

===== First Aid Measures =====

First Aid:SKIN/EYES: FLUSH W/WATER. INHALATION: REMOVE TO FRESH AIR.
OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:100F
Lower Limits:1.1
Extinguishing Media:SMALL FIRES: CO2/DRY CHEMICAL. LARGE FIRES: FOAM
Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS FOR
FIREMEN.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID
BREATHING VAPORS. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE ABOVE 120F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE
FLAMMABLES.
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID
FREE FALL OF LIQUID IN EXCESS OF FEW INCHES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR/AIR

SUPPLIED

RESPIRATOR. RESPIRATOR USED BASED ON CHEMICAL CONDITION & CONDITIONS OF USE.

Ventilation:PROVIDE GENERAL DILUTION/LOCAL EXHAUST AS NECESSARY.

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:270-390F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:54

===== Sta
bility and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:FIRE, HEAT, HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.