View NSN Online: https://aerobasegroup.ae/nsn/9150-00-235-5568

NONFLUID OIL CORP. -- VV-G-671 (GREASE, GRAPHITE) -- 9150-00-235-5568

Product ID:VV-G-671 (GREASE, GRAPHITE) MSDS Date:12/01/1986 FSC:9150 NIIN:00-235-5568 **MSDS Number: BDLPM** === Responsible Party === Company Name: NONFLUID OIL CORP. Address:298 DELANCY ST **City:NEWARK** State:NJ ZIP:07105 Country:US Info Phone Num:(201)344-3451 Emergency Phone Num: (201) 344-3451 CAGE:7 6736 === Contractor Identification === Company Name: NONFLUID OIL CORP/NFO TECHNOLOGIES, INC Address:298 DELANCY ST **City:NEWARK** State:NJ ZIP:07105-3009 Country:US Phone:201-344-3451/800-424-9300(CHEMTREC) CAGE:76736

Ingred Name:NON-HAZARDOUS COMPONENTS (PER MSDS)SEE INGREDIENTS #2,3 AND 4 AS GIVEN IN CTDF Other REC Limits:5MG/CUM AS OIL MIST

Ingred Name:CALCIUM SOAP (USED AS THICKENER)

Ingred Name:GRAPHITE, NATURAL CAS:7

782-42-5
RTECS #:MD9659600
OSHA PEL:15 MPPCF RDUST
ACGIH TLV:2 MG/M3 RDUST; 9293

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST') CAS:8012-95-1 RTECS #:PY8030000 Other REC Limits:5MG/CUM AS OILMIST OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3/10 STEL;9192

	Hazards Identification	
--	------------------------	--

Health Hazards Acute and Chronic:AS WITH ALL PETROLEUM PRODUCTS,PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE MILD IRRITATION. DEFATTING ON SKIN IS POSSIBLE. EXPOSUR E TO FUMES OR MISTS MAY CAUSE MUCOUS MEMBRANE IRRITATION. Effects of Overexposure:MILD IRRITATION OF SKIN AND MUCOUS MEMBRANE.

First Aid:EYE:FLUSH WITH LARGE AMOUNTS OF WATER AND SEE A DOCTOR;SKIN:WIPE OFF AND WASH WITH SOAP AND WATER;INHALATION:REMOVE TO FRESH AIR;INGESTION:GIVE WATER & SEEK MEDICAL AID.

Flash Point Method:COC Flash Point:410F ,210C Lower Limits:1 Upper Limits:6 Extinguishing Media:CO*2,DRY CHEMICAL,FOAM AND WATER FOG (CAREFULLY TO PREVENT FROTHING) Fire Fighting Procedures:WEAR SCBA WITH FACE SHIELD IN ENCLOSED AREAS. Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures:STOP FLOW. ELIMINATE IGNITION SOURCES. RECOVER FREE PRODUCT. ADD ABSORBENT MATERIAL SUCH AS CLAY TO SPILL AREA. SWEEP OR SCRAPE UP.

======= Handli

Handling and Storage Precautions: KEEP CONTAINERS CLOSED. HANDLE AND STORE AS PETROLEUM PRODUCTS. DO NOT STORE OR MIX WITH OXIDIZING MATERIALS. AVOID EXCESSIVE HEAT OR FLAMES.

Other Precautions: AVOID REPEATED CONTACT WITH SKIN. AVOID CONTACT WITH EYES & INHALATION OF FUMES, VAPORS OR MISTS. DO NOT INGEST.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NORMALLY NOT REQUIRED. RECOMMENDED IF FUMING OR

MISTING.

Ventilation:LOCAL EXHAUST & MECHANICAL(GENERAL) RECOMMENDED. Protective Gloves:GLOVES RECOMMENDED FOR REPEATED CONTACT. Eye Protection:GOGGLES RECOMMENDED IF SPLASHING OR MIST Other Protective Equipment:NORMALLY NOT REQUIRED. PROTECTIVE CLOTH RECOMMENDED IF FUMING OR MISTING.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING. DO NOT WEAR CONTAMINATED CLOTHING. REMOVE AND LAUNDER BEFORE REUSE. Supplemental Safety and Health

============= Physical/Chemical Properties

HCC:V6 Vapor Pres:0.01 Vapor Density:11 Spec Gravity:0.92 Evaporation Rate & amp; Reference:NEGLIGIBLE Solubility in Water:NEGLIGIBLE Appearance and Odor:BLACK SEMI-SOLID PASTE. SLIGHT PETROLEUM ODOR.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:EXCESSIVE HEAT & OPEN FLAMES. Hazardous Decomposition Products:CO,CO*2

====== Disposal Consider

Waste Disposal Methods:DISPOSE OF IAW FEDERAL,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advi ce to verify and

assume responsibility for the suitability of this information to their particular situation.