E.I. DUPONT DE NEMOURS AND CO, INC -- SULFURIC ACID, 77 TO 100% -- 6810-00-236-0702

Product ID:SULFURIC ACID, 77 TO 100% MSDS Date:10/01/1988 FSC:6810 NIIN:00-236-0702 MSDS Number: BDLRZ === Responsible Party === Company Name: E.I. DUPONT DE NEMOURS AND CO, INC Address:1007 MARKET STREET Box:1635 City:WILMINGTON State:DE ZIP:19899 Country:US Info Phone Num:800-441 -9442 Emergency Phone Num:800-441-3637 Preparer's Name: J. C. WATTS CAGE:19898 === Contractor Identification === Company Name: E.I. DUPONT DE NEMOURS & CO Address:1007 MARKET STREET Box:City:WILMINGTON State:DE ZIP:19898 Country:US Phone:800-441-7515;800-441-9442 CAGE:18873 Company Name: E.I. DUPONT DE NEMOURS & CO., INC. Box:1635 CAGE:19898 Company Name: INLAND PACKAGING INC Address:209 PETERSON DR Box:644 City:ELIZABETHTOWN State:KY ZIP:42701-9804 Country:US Phone:502-737-6757 CAGE:66172

=======

===== Composition/Information on Ingredients ==========

Ingred Name:SULFURIC ACID (SARA III) CAS:7664-93-9 RTECS #:WS5600000 Fraction by Wt: 29.5% OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 70.5% LD50 LC50 Mixture:LD50 (ORAL RAT) IS 2140 MG/KG Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO **Reports of Carci** nogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: INHALATION OF VAPORS MAY CAUSE SEVERE IRRITATION OR BURNS OF THE RESPIRATORY SYSTEM, PULMONARY EDEMA, OR LUNG INFLAMMATION. MAY CAUSE SEVERE BURNS TO SKIN OR EYES. INGESTION MAY CAUSE SEVERE BU RNS TO MOUTH, THROAT, AND STOMACH. MAY AFFECT KIDNEY FUNCTION. CHRONIC: MAY DAMAGE LUNGS. Explanation of Carcinogenicity: THIS PRODUCT IS NOT LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN. Effects of Overexposur e:SEVERE IRRITATION OR BURNS TO EYES, NOSE AND THROAT. PULMONARY EDEMA, BRONCHIAL EMPHYSEMA, CONJUNCTIVITIS, STOMATITIS, DENTAL EROSION, NAUSEA AND VOMITING. Medical Cond Aggravated by Exposure: PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid:INHALATION: REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING. GET MEDICAL ATTENTION. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: REM OVE CONTAMINATED CLOTHING. WASH WITH PLENTY OF WATER FOR 15 MINUTES. GET MEDICAL ADVICE. INGESTION: DO NOT INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

Flash Point:WILL NOT BURN
Extinguishing Media:USE MEDIA AS APPROPRIATE FOR COMBU
STIBLES IN AREA.
USE WATER SPRAY TO COOL CONTAINERS EXPOSED TO FIRE.
Fire Fighting Procedures:EVACUATE PERSONNEL TO A SAFE AREA. KEEP
PERSONNEL REMOVED AND UPWIND OF FIRE. WEAR FULL PROTECTIVE
CLOTHING. RUNOFF FROM FIRE CONTROL MAY CAUSE POLLUTION.
Unusual Fire/Explosion Hazard:REACTS WITH MOST METALS, ESPECIALLY WHEN
DILUTE, TO GIVE FLAMMABLE, POTENTIALLY EXPLOSIVE HYDROGEN GAS. DO
NOT GET WATER INSIDE CONTAINERS.

======

Spill Release Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. STOP LEAK IF YOU CAN DO SO WITHOUT RISK. DO NOT USE WATER. NEUTRALIZE SPILL AND/OR WASHINGS WITHN SODA ASH OR LIME. WITH CLEAN SHO VEL, PLACE MATERIAL INTO CLEAN, DRY CONTAINER.

Neutralizing Agent:LIME OR SODA ASH

Handling and Storage Precautions: KEEP CONTAINER TIGHTLY CLOSED. STORE IN CORROSION-PROOF ARE

A. KEEP CONTAINERS OUT OF SUN AND AWAY FROM HEAT. ISOLATE FROM INCOMPATIBLE MATERIALS.

Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. DO NOT BREATHE VAPOR. KEEP IN TIGHTLY CLOSED CONTAINER. LOOSEN CLOSURE CAUTIOUSLY. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. IN CASE OF SPILL NEUTRALIZE WITH SODA ASH OR LIME.

Respiratory Protection:NONE REQUIRED WHERE ADEQUATE VENTILATION

CONDITIONS EXIST. IF AIRBORNE CONCENTRATION EXCEEDS TLV, A NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED. Ventilation: USE MECHANICAL (GENERAL) OR LOCAL EXHAUST VENTILATION TO MEET TLV REQUIREMENTS. Protective Gloves: RUBBER Eye Protection: SAFETY GOGGLES WITH OPTIONAL FACE SHIELD Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED. Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND R ECOMMENDED PROCEDURES. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS. HCC:C1 Boiling Pt:B.P. Text:380F,193C Melt/Freeze Pt:M.P/F.P Text:-31F,-35C Vapor Pres:< 0.3

Vapor Density:3.4 Spec Gravity:1.21 pH:< 1.0 Evaporation Rate & Reference:< 1 (BUTYL ACETATE = 1) Solubility in Water:COMPLETE Ap pearance and Odor:OILY, CLEAR TO TURBID, COLORLESS TO LIGHT GRAY LIQUID WITHNO ODOR.

Stability Indicator/Materials to Avoid:YES WATER, ALKALINE SOLUTIONS, METALS, METAL POWDERS, CARBIDES, CHLORATES, FULMINATES, NITRATES, PICRATES, ORGANIC MATERIALS Stability Condition to Avoid:HIGH HEAT, MOISTURE Hazardous Decomposition Products:OXIDES OF SULFUR, HYDROGEN SULFIDE, HYDROGEN GAS

====== Disposal Consid

erations ================

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL ENVIRONMENTAL REGULATIONS. DO NOT FLUSH TO SURFACE WATER OR SANITARY SEWER SYSTEM.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accu rate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.