

E.I. DUPONT DE NEMOURS & CO, INC. -- NITRIC ACID,40 DEG BAUME -- 6810-00-236-5670

===== Product Identification =====

Product ID:NITRIC ACID,40 DEG BAUME

MSDS Date:10/01/1985

FSC:6810

NIIN:00-236-5670

MSDS Number: BDLTZ

=== Responsible Party ===

Company Name:E.I. DUPONT DE NEMOURS & CO, INC.

Address:1007 MARKET STREET

Box:1635

City:WILMINGTON

State:DE

ZIP:19899

Country:US

Info Phone Num:800-441-944

2 OR 302-999-4946

Emergency Phone Num:800-441-3637

Preparer's Name:J.C. WATTS

CAGE:19898

=== Contractor Identification ===

Company Name:E.I. DUPONT DE NEMOURS & CO

Address:1007 MARKET STREET

Box:City:WILMINGTON

State:DE

ZIP:19898

Country:US

Phone:800-441-7515;800-441-9442

CAGE:18873

Company Name:E.I. DUPONT DE NEMOURS & CO., INC.

Box:1635

CAGE:19898

Company Name:VAN WATERS AND ROGERS DIV OF UNIVAR CORP.

Address:650 W 8TH SOUTH

Box:2369

City:SALT LAKE CITY

State:UT

ZIP:84110

Country:US

Phone:801-

328-1112/CHEMTREC 800-424-9300
CAGE:5T823

===== Composition/Information on Ingredients =====

Ingred Name:NITRIC ACID (SARA III)
CAS:7697-37-2
RTECS #:QU5775000
Fraction by Wt: 61.4%
OSHA PEL:2 PPM/4 STEL
ACGIH TLV:2 PPM/4 STEL; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: BALANCE

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL: 50-500 MG/KG
Routes of Entry: Inha
lation:YES Skin:UNKNOWN Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:CORROSIVE TO ALL BODY
TISSUES;SKIN: IRRITATION,RASH;EYES:IRRITATION,TEARING,BLURRING OF
VISION;IRRITATION OF RESPIRATORY TRACT OR G.I.TRACT.
CHRONIC:HARMFUL,TISSUE AND LUNGS DAMAGE.
Effects of Overexposure:LIQ & VAPOR CAUSES SEVERE BURNS.HARNFUL IF
INHALED.W LUNG INJURY.MAY PRODUCE DANGEROUS TOXIC GASES.
Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE
WORSEN.

=====

==== First Aid Measures =====

First Aid:SKIN/EYES:FLUSH W PLENTY WATER.INHALED: REMOVE TO FRESH
AIR.GIVE CPR/02 IF NEED.REMOVE & WASH CONTAMINATED CLOTHES.GIVE LG
AMTS WATER W MILK OF MAGNESIA,MILK,MGO,EGG WHITES OLIVE OIL.DO NOT
INDUCE VOM ITING.AVOID CARBONATES CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:FOR FIRE IN AREA,USE WATER SPRAY TO COOL CONTAINERS
Fire Fighting Procedures:

WEAR CHEMICAL PROTECTIVE SUIT WITH SELF CONTD
BRTHG APP.

Unusual Fire/Explosion Hazard:OXIDIZER INCREASES COMBUSTIBILITY.CAN
IGNITE COMBUST,OXID MATL.MAY PRODUCE TOXIC GAS.METALS GIV H2

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK W/O
RISK. EVACUATE AREA. SM SPILL:ABSORB WITH INERT ABSORBENT,FLUSH
AREA WITH WATER. LG SPILL:NEUTRALIZE WITH SODA ASH. FLUSH
NEUTRALIZED SOLUTION TO SEWER IN AC
CORDANCE WITH INTERNATIONAL
FED,STA, & LOCAL REGS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENT,LOW FIRE
RISK AREA. PROTECT CONTRS FROM PHYS DAMAGE.KEEP OUT OF DIR RAYS OF
SUN AWAY FR ORG PROD & OTHER EASILY OXID MATL

Other Precautions:SEN CLOSURES CAREFULLY.NEVER USE PRESSURE TO
EMPTY.WASH CONTAINERS BEFORE RE-USE.DO NOT BREATH VAPOR.AVOID
CONTACT.WASH THOROUGHLY AFTER HANDLING.REFER TO DU
PONT NITRIC ACID
DATA SHEET.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SCBA, SUPPLIED AIR RESPIRATOR

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves:RUBBER

Eye Protection:CHEM SPLASH GOGGLES

Other Protective Equipment:RUBBER BOOTS,FULL PROTECTIVE CLOTHNG,HARD
HAT, CHEMICAL SUIT.

Supplemental Safety and Health

38 DEG BE:BOILING POINT:117-243F & SP. GRAVITY =1.355 (56.5%). 40 DEG
BE:BOILING POINT:119-246F & SP.GRAVITY

= 1.381 (61.4%). 42 DEG

BE:BOILING POINT:120-248F & SP.GRAVITY =1.408 (67.2%)

===== Physical/Chemical Properties =====

HCC:C1

Boiling Pt:B.P. Text:246F,119C

Melt/Freeze Pt:M.P/F.P Text:-12F,-24C

Vapor Pres:9.5

Vapor Density:1.0

Spec Gravity:1.381

pH:1.0

Evaporation Rate & Reference:APPROX 1 (BUTYL ACETATE)

Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS-LIGHT BROWN CLEAR LIQUID WITH AN ACRID
ODOR.

Percent Volatiles by Volume:100

=====

==== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

CYANIDES, SULFIDES, ORGANICS, METALS, CARBIDES, OXIDIZABLE MATL.

Stability Condition to Avoid: HEAT, IGNITION SOURCES

Hazardous Decomposition Products: NITROGEN OXIDES AND OTHER OXIDES;
TOXIC FUMES; FLAM GAS

===== Disposal Considerations =====

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE &
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE

INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.