View NSN Online: https://aerobasegroup.ae/nsn/6810-00-241-1193

Product ID:NITRIC ACID STRONG MSDS Date:11/01/1987 FSC:6810 NIIN:00-241-1193 MSDS Number: BDMLZ === Responsible Party === Company Name: E.I. DUPONT DE NEMOURS & CO, INC. Address:1007 MARKET STREET Box:1635 **City:WILMINGTON** State:DE ZIP:19899 Country:US Info Phone Num:800-441-9442 Emergency Ph one Num:800-441-3637(800-424-9300 CHEMTREC) Preparer's Name: J.C. WATTS CAGE:19898 === Contractor Identification === Company Name: E.I. DUPONT DE NEMOURS & CO Address:1007 MARKET STREET Box:City:WILMINGTON State:DE ZIP:19898 Country:US Phone:800-441-7515;800-441-9442 CAGE:18873 Company Name: E.I. DUPONT DE NEMOURS & CO., INC. Box:1635 CAGE:19898

Ingred Name:NITRIC ACID (SARA III) CAS:7697-37-2 RTECS #:QU5775000 Fraction by Wt: > 90% OSHA PEL:2 PPM/4 STEL ACGIH TLV:2 PPM/4 STEL; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

LD50 LC50 Mixture:ORAL LD50 (RAT) IS 50-500 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: MAY CAUSE IRRRITATION OR BURNS TO SKIN AND EYES BOTH FROM VAPORS AND CONTACT WITH LIQUID. INHALATION OF VAPORS MAY CAUSE IRRITATION OF UPPER RESPIRATORY TRACT. INGESTION MAY CAUSE SEVERE DAMAGE TO MUC OUS IN MOUTH, THROAT AND ESOPHAGUS; SEVERE GI TRACT IRRITATION. Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN. Effects of Overexposure: INHALATION: SNEEZING, WHEEZING, COUGHING, SHORTNESS OF BREATH. EYES: BURNING SENSATION, TEARING, PAIN, REDNESS. SKIN: REDNESS, PAIN. INGESTED: BURNING SENSATION OF MOUTH, THROAT, AND ES OPHAGUS; SEVERE STOMACH PAIN, NAUSEA, VOMITING. Medical Cond Aggravated by Exposure: PERSONS WITH PRE-EXISTING RESPIRATORY DISORDERS MAY HAVE INCREASED SUSCEPTIBLITY TO EFFECTS OF THIS MATERIAL.

First Aid:INHALED: REMOVE PERSON TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING DIFFICULT, GIVE OXYGEN. SEE DOCTOR. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: RE MOV

E CONTAMINATED CLOTHES. FLUSH WITH LOTS OF WATER. SEE DOCTOR. INGESTED: DO NOT INDUCE VOMITING! IF CONSCIOUS, GIVE LARGE QUANTITY OF WATER. GET IMMEDIATE MEDICAL ATTENTION.

 Extinguishing Media:WATER, DRY CHEMICAL, OR SODA ASH. USE WATER SPRAY TO COOL CONTAINERS AND REDUCE VAPORS.
Fire Fighting Procedures:WEAR FULL ACID PROTECTIVE CLOTHING AND SELF-CONTAINED BREATHING APPARATUS WHERE CONTACT WITH FUMES OR ACID EXISTS. RUN-OFF FROM MAY CAUSE POLLUTION. Unusual Fire/Explosion Hazard:NITRIC ACID INCREASES THE FLAMMABILITY OF AND CAN IGNITE MANY ORGANIC MATERIALS SUCH AS WOOD, SOLVENTS, ETC AND CAN RELEASE TOXIC OXIDES OF NITROGEN.

Spill Release Procedures: EVACUATE AREA. ISOLATE AND DENY ENTRY. WEAR SCBA AND CHEMICAL PROTECTIVE CLOTHING. CONTAIN SPILL. FLUSH AREA WITH LARGE AMOUNT OF WATER. NEUTRALIZE WASHINGS WITH S ODA ASH OR

LIME. DO NOT FLUSH TO SEWE R. REPORT, IF REQUIRED. Neutralizing Agent:SODA ASH OR LIME

Handling and Storage Precautions: KEEP CONTAINERS CLOSED. KEEP AWAY FROM HEAT, SPARKS, AND FLAME. DO NOT STORE NEAR INCOMPATIBLES. DO NOT PRESSURIZE TO EMPTY.

Other Precautions: CONTAINERS MUST NOT BE WASHED OUT OR USED FOR OTHER PURPOSES. LOOSEN CLOSURES CAREFULLY.

======= Exposure Controls/Personal Protecti

on ==========

Respiratory Protection: IN AN EMERGENCY USE NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS.

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves:NEOPRENE

Eye Protection: GOGGLES/FACE SHIELD

Other Protective Equipment: (FOR EMERGENCIES) WEAR FULL COVERING ACID-RESISTENT SUIT WITH RUBBER BOOTS. EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices: WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFOR E REUSE.

Supplemental Safety and Health

FOR DAILY PROTECTION: USE APRON, NEOPRENE GLOVES. MIL-STD-1218 ALSO APPLIES.

HCC:D4 Boiling Pt:B.P. Text:185F,85C Melt/Freeze Pt:M.P/F.P Text:-45F,-43C Vapor Pres:51MMHG@77F Vapor Density:>1(AIR=1) Spec Gravity:1.5 pH:1 Evaporation Rate & amp; Reference:>1 (N-BUTYL ACETATE=1) Solubility in Water:COMPLETE Appearance and Odor:COLORLESS TO LIGHT BROWN CLEAR LIQUID. ACRID ODOR.

=======

Stability Indicator/Materials to Avoid:YES OXIDIZABLE MATERIALS, ORGANIC SOLVENTS, METAL POWDERS, CARBIDES, CYANIDES, SULFIDES, AND ALKALIES. Stability Condition to Avoid:HEAT-RELEASES TOXIC GASES. Hazardous Decomposition Products:OXIDES OF NITROGEN

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. IF APPROVEE, DRAIN N EUTRALIZED WASHINGS TO A WASTE TREATMENT PLANT OR TRANSFER TO A DISPOSAL CONTRACTOR.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.