

HERCULITE PRODUCTS INC -- TURPENTINE (ASTM D-13) -- 8010-00-246-6443

=====  
Product Identification  
=====

Product ID:TURPENTINE (ASTM D-13)  
MSDS Date:01/01/1985  
FSC:8010  
NIIN:00-246-6443  
MSDS Number: BDNJW  
=== Responsible Party ===  
Company Name:HERCULITE PRODUCTS INC  
Address:ABEERDEEN RD  
Box:467  
City:EMIGSVILLE  
State:PA  
ZIP:17318  
Country:US  
Info Phone Num:717-764-1191/FAX 717-764-5211  
Emergency Phon  
e Num:717-764-1191/FAX 717-764-5211  
CAGE:13324

==== Contractor Identification ===  
Company Name:HERCULES INCORPORATED  
Address:HERCULES PLAZA  
City:WILMINGTON  
State:DE  
ZIP:19894  
Country:US  
Phone:302-594-5000  
CAGE:28284  
Company Name:HERCULITE PRODUCTS INC  
Address:1107 BROADWAY  
Box:467  
City:NEW YORK  
State:NY  
ZIP:10010-2802  
Country:US  
CAGE:13324

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SOLVENTS  
Fraction by Wt: 100%  
ACGIH TLV:100PPM

=====  
Hazar

ds Identification =====

Effects of Overexposure:MAY CAUSE EYE IRRITATION DERMITITAS OF SKIN,MAY CAUSE KIDNEY INFECTIONS.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/WATER,CALL A DR.SKIN:WASH W/SOAP & WATER.INHAL:REMOVE TO FRESH AIR.IF SWALLOWED:DO NOT INDUCE VOMITING,

===== Fire Fighting Measures =====

Flash Point:99F TCC 37 C  
Extinguishing Media:FOAM,DRY CHEMICAL,CO\*2

=====

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCE.STOP SPILL AT ONCE,CONTAIN SPILL BY DIKE,ETC.PUMP INTO SALVAGE TANK.AVOID CONTACT W/VAPOR OR SPRAY MIST.

===== Handling and Storage =====

Handling and Storage Precautions:NORMAL,KEEP AWAY FROM FLAMES OR HIGH HEAT.USE ONLY W/ADEQUATE VENTILATION.AVOID PROLONGED CONTACT W/SKIN.

Other Precautions:AVOID CONTACT W/OXIDIZING MATERIALS.

=====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AS NEEDED TO MAINTAIN CONCENTT BELOW TLV LEVEL

Ventilation:LOC EXHAUST-RECOMMENDED

Protective Gloves:RECOMMENDED

Eye Protection:RECOMMENDED

Supplemental Safety and Health

PROCURED UNDER ASTM D-13

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:307 F 152 C

Spec Gravity:.864

Evaporation Rate & Reference:1

Solubility in Water:NEGLIGIBLE

Appearance and Odor:SLI

GHTLY YELLOW COLOR W/A PINACEOUS ODOR

Percent Volatiles by Volume:99.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:STRONG OXIDIZING MATERIALS

Conditions to Avoid Polymerization:CONTACT W/STRONG ACIDS FOR LEWIS  
ACIDS

===== Disposal Considerations =====

Waste Disposal Methods:LIQUID INCINERATION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.