

SILBERLINE MFG CO, PANTHER VAL IND PK, LANSFORD PA -- AL PASTE -- 8010-00-247-4347

=====
Product Identification
=====

Product ID:AL PASTE

MSDS Date:01/01/1987

FSC:8010

NIIN:00-247-4347

MSDS Number: BDNMW

=== Responsible Party ===

Company Name:SILBERLINE MFG CO, PANTHER VAL IND PK, LANSFORD PA

Emergency Phone Num:717-645-3161

CAGE:97827

=== Contractor Identification ===

Company Name:SILBERLINE MFG

CO INC

Address:PANTHER VALLEY INDUSTRIAL PK

Box:A

City:LANSFORD

State:PA

ZIP:18232

Country:US

CAGE:97827

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 35.0%

OSHA PEL:100 PPM

Ingred Name:ALUMINUM (SARA III)

CAS:7429-90-5

RTECS #:BD0330000

Fraction by Wt: 65.0%

OSHA PEL:15MG/M3 DUST/5 FUME

ACGIH TLV:10MG/M3 DUST; 9192

=====
Hazards Identification
=====

=====

Effects of Overexposure:IRRITATION TO EYES AND SKIN;BREATHING PROBLEMS FROM INHALATION

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER TO REMOVE IRRITANT.GET MEDICAL HELP AS SOON AS POSSIBLE.SKIN: FLUSH WITH WATER,WASH WITH MILD SOAP AND RINSE WITH WATER.APPLY A GOOD QUALITY HAND CREAM.INHALATION:REMOVE VICTIM F ROM CONTAMINATED AREA.KEEP WARM.CALL DOCTOR.

===== Fire Fighting Measures =====

=====

Flash Point:105F TCC

Lower Limits:1.0

Upper Limits:6.0

Fire Fighting Procedures:DO NOT USE-CARBON TETRACHLORIDE AS A FIRE EXTINGUISHER/WATER

Unusual Fire/Explosion Hazard:IN CLOSED CONTAINERS PRESSURE BUILD-UP IS POSSIBLE WHEN EXPOSED TO EXCESSIVE HEAT.WATER TO COOL CONT

===== Accidental Release Measures =====

Spill Release Procedures:REPACK UNCONTAMINATED MATERIAL IN A DRY,TIGHTLY SEALED CONTAINER. CHECK FOR QUALITY.USE NON-SPARKING TOOLS AND REMOVE ALL SPARKS,FLAMES AND HOT SURFACES FROM AREA.

===== Handling and Storage =====

Other Precautions:DO NOT TAKE INTERNALLY;AVOID PROLONGED CONTACT WITH SKIN,ETC.USE NON-SPARKING METAL SCOOPS OR SHOVELS FOR TRANSFER.ALL EQUIPMENT SHOULD BE WELL GROUNDED.

===== Exposure Controls/Personal Protection =====

Ventilation:GENER DILUTION TYPE VENT ADEQUATE TO KEEP VAPOR CONC DOWN

Protective Gloves:YES

Eye Protection:SAFETY

GLASSES

Other Protective Equipment:PROT. HAND CREAM FOR SKIN CONTACT AREAS.

Supplemental Safety and Health

STATEMENT FROM SILBERLINE MFG CO.: SEE FIRE PROTECTION GUIDE ON
HAZARDOUS MATERIALS, NFPA, SECTION 491M, ALUMINUM

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:326F

Vapor Density:>1

Spec Gravity:>1

Solubility in Water:NO

Appearance and Odor:SOFT ALUMINUM PASTE-MINERAL SPIRITS ODOR

===== Stability and Reactivity Data ==

=====

WATER,ACIDS AND ALKALIS

Stability Condition to Avoid:KEEP STORAGE RM OF WATER VAPOR/POSS CONTAM
VAPORS/GASES

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:SANITARY LANDFILL IN ACCORDANCE WITH LOCAL,STATE
AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The

United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.