View NSN Online: https://aerobasegroup.com/nsn/8010-00-248-2838

AMERON PROTECTIVE COATINGS -- YELLOW 13538 -- 8010-00-248-2838

Product ID:YELLOW 13538 MSDS Date:01/01/1987 FSC:8010 NIIN:00-248-2838 MSDS Number: BDNPK === Responsible Party === Company Name: AMERON PROTECTIVE COATINGS Address:201 NORTH BERRY STREET City:BREA State:CA ZIP:92622-1020 Country:US Info Phone Num:714-529-1951 Emergency Phone Num:714-529-1951 CAGE:0Y2 E4 === Contractor Identification === Company Name: AMERON PROTECTIVE COATINGS Address:201 NORTH BERRY STREET Box:1020 City:BREA State:CA ZIP:92622-1020 Country:US Phone:714-529-1951 CAGE:0Y2E4 Ingred Name: ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL CARBINOL (IARC-GROUP 3) *97-3* CAS:67-63-0 RTECS #:NT8050000 Fraction by Wt: 9.0% Other REC Limits:400 PPM OSHA PEL:400 PPM ACGIH TLV:400 PPM Ingred Name:ALIPHAATIC

NAPHTHA Fraction by Wt: 5.0%

Ingred Name: ISOBUTYL ACETATE CAS:110-19-0 RTECS #:AI4025000 Fraction by Wt: 7.0% Other REC Limits:150 PPM **OSHA PEL:150 PPM** ACGIH TLV:713 MG/CUM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: TOLUENE (IARC CARC- GROUP 3) *97-3* CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 8.0% Other REC Limits:375 MG/CUM OSHA PEL:100 PPM ACGIH TLV:100 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: METHYL ETHYL KETONE, 2-BUTANONE *97-3* CAS:78-93-3 RTECS #: EL6475000 Fraction by Wt: 18.0% Other REC Limits:590 MG/CUM OSHA PEL:200 PPM ACGIH TLV:590 MG/CUM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: ANESTHETIC. IRRITATION OF RESPIRATORY TRACT & MAY CAUSE NERVOUS SYSTEM DEPRESSION. SKIN/EYES: IRRITATION. Explanation of Carcinoge

nicity:NONE Effects of Overexposure:IRRITATION

======================================
First Aid:SKIN/EYES: FLUSH W/WATER. INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.
======================================
Flash Point Method:TCC Flash Point:30F Lower Limits:1.1 Extinguishing Media:SMALL FIRES: CO2/DRY CHEMICAL. LARGE FIRES: FOAM Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS. Unusual F ire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE.
======================================
Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.
======================================
Handling and Storage Precautions:DON'T STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLES. Othe
r Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.
======================================
Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR/AIR SUPPLIED RESPIRATOR. Ventilation:PROVIDE GENERAL DILUTION/LOCAL EXHAUST AS NECESSARY. Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health

================= Physical/Chemical Properties =

Boiling Pt:B.P. Text:118-321F Vapor Density:>1 Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:75.0

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:FIRE, HEAT, HOT SURFACES

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CO NTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particu

lar situation.