

J. C. ENTERPRISES, INCORPORATED -- ENTERPRISE 1000;LUBRICATING OIL,WATCH --  
9150-00-252-6382

=====  
===== Product Identification =====

Product ID:ENTERPRISE 1000;LUBRICATING OIL,WATCH

MSDS Date:01/01/1987

FSC:9150

NIIN:00-252-6382

MSDS Number: BDNYC

=== Responsible Party ===

Company Name:J. C. ENTERPRISES, INCORPORATED

Address:724 WESTCLIFF ROAD

Box:7345

City:WILMINGTON

State:DE

ZIP:19803-1712

Country:US

Info Phone Num:302-478-8326

Emergency Phone Num:302-478-8326

CAGE:KO867

=== Contractor Identification ===

Company Name:J C ENTERPRISES INC

Address:724 WESTCLIFF RD

Box:7345

City:WILMINGTON

State:DE

ZIP:19803-1712

Country:US

Phone:302-478-8326

CAGE:2S598

Company Name:J. C. ENTERPRISES, INCORPORATED

Address:724 WESTCLIFF ROAD

Box:7345

City:WILMINGTON

State:DE

ZIP:19803-1712

Country:US

Phone:302-478-8326

CAGE:KO867

=====  
===== Composition/Information on Ingredients =====

Ingred Name:BE

NZYL PHENYLUNDECANOATE

Fraction by Wt: 59.9%

Ingred Name:DIETHYLENE GLYCOL DI-N-CAPROATE

Fraction by Wt: 39.5%

Ingred Name:DODECYLIPIPERIDINE STEARATE

Fraction by Wt: 0.4%

Ingred Name:P-TERTIARY-BUTYL CATECHOL

Fraction by Wt: 0.2%

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:ACUTE: IRRITATION OF EYES OR SKIN  
POSSIBLE. CHRONIC: NO DATA AVAILABLE.  
Medical Cond Aggravated by  
Exposure:PRE-EXISTING CONDITIONS MAY BE  
WORSEN.

=====  
===== First Aid Measures =====

First Aid:EYE: FLUSH OUT W/WATER; GET MEDICAL ATTENTION IMMEDIATELY;  
INHALATION: NONE; INGESTION: NONE IDENTIFIED

=====  
===== Fire Fighting Measures =====

Flash Point:>392F/200C  
Extinguishing Media:CO\*2, FOAM, DRY CHEM.  
Fire Fighting Procedures:NONE  
Unusual Fire/Explosion Hazard:NONE WHEN USED AS A LUBRICATING OIL FOR  
INSTRUMENTS,JEWEL  
BEARING,NON-SPREADING APPLICATION.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN LIQUID,COVER WITH OIL DRY  
COMPOUND,SWEEP-UP

=====  
===== Handling and Storage =====

Handling and Storage Precautions:USE NORMAL TECHNIQUES FOR HANDLING  
ORGANIC CHEMICALS WHICH ARE USED AS LUBRICATING OILS. LONG TERM  
STORAGE IN SUNLIGHT WILL CAUSE COLOR CHANGE.

=====  
===== Exposure Controls/Personal Protection =====

=====

Respiratory Protection:NONE SHOULD BE NEEDED

Ventilation:NORMAL ROOM VENTILATION.

Protective Gloves:NONE

Eye Protection:SAFETY GLASSES

Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.

Supplemental Safety and Health

MSDS DATE:UNKOWN; STABILITY: 2 YR. SHLF-LFE MINIM; SUNLIGHT(LONG TERM STORAGE IN) CAUSES COLOR CHANGE FROM YELLOW TO ORANGE(PERFORMANCE NOT AFFECTED)

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Te

xt:VERY HIGH

Evaporation Rate & Reference:@ 210F/99C