View NSN Online: https://aerobasegroup.com/nsn/8010-00-257-5377

AMERON PROTECTIVE COATINGS -- WHITE 17875 -- 8010-00-257-5377

Product ID:WHITE 17875 MSDS Date:01/01/1987

FSC:8010

NIIN:00-257-5377

MSDS Number: BDPJZ === Responsible Party ===

Company Name: AMERON PROTECTIVE COATINGS

Address: 201 NORTH BERRY STREET

City:BREA State:CA

ZIP:92622-1020 Country:US

Info Phone Num:714-529-1951

Emergency Phone Num:714-529-1951

CAGE:0Y2E4

=== Contractor Identification ===

Company Name: AMERON PROTECTIVE COATINGS

Address: 201 NORTH BERRY STREET

Box:1020 City:BREA State:CA

ZIP:92622-1020 Country:US

Phone:714-529-1951

CAGE:0Y2E4

======= Composition/Information on Ingredients ========

Ingred Name: ISOBUTANOL, 2-METHYL-1-PROPANOL, ISOBUTYL ALCOHOL

CAS:78-83-1

RTECS #:NP9625000 Fraction by Wt: 8.0% Other REC Limits:50 PPM OSHA PEL:300 MG/CUM ACGIH TLV:152 MG/CUM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:BENZIN

, NAPHTHA, MINERAL SPIRITS, PETROLEUM NAPHTHA

CAS:8030-30-6

RTECS #:DE3030000 Fraction by Wt: 6.0%

Other REC Limits: STEL 400 PPM

OSHA PEL:100 PPM ACGIH TLV:300 PPM

Ingred Name: BUTYL ACETATE (N-BUTYL ACETATE) *98-1*

CAS:123-86-4

RTECS #:AF7350000 Fraction by Wt: 25.0% Other REC Limits:150 PPM OSHA PEL:710 MG/CUM ACGIH TLV:713 MG/CUM EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name: ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL

CARBINOL (IARC-GROUP 3) *98-2*

CAS:67-63-0

RTECS

#:NT8050000

Fraction by Wt: 7.0%

Other REC Limits:400 PPM

OSHA PEL:400 PPM ACGIH TLV:400 PPM

Ingred Name: ETHYL BENZENE *98-2*

CAS:100-41-4

RTECS #:DA0700000 Fraction by Wt: LT5% Other REC Limits:100 PPM OSHA PEL:435 MG/CUM ACGIH TLV:434 MG/CUM EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

========= Hazards Identification ==============

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Explanation of Carcinogenicity:NONE

Effects of Overexposure:ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION
======================================
First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CALL A PHYSICIAN IF CONDITIONS PERSIST
======================================
Flash Point Method:TCC Flash Point:30F Lower Limits:1.1 Exting
uishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE
FIRES-FOAM Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE
========= Accidental Release Measures ============
Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS
======================================
Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLES.
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECES

Stability Condition to Avoid:AVOID FIRE, HEAT AND HOT SURFACES

SARY

====== Disposal Considerations ==========

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims

all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.