

CALUMET REFINING CO DIV OF CALUMENT INDUSTRIES INC -- FOG OIL -- 9150-00-261-7895  
===== Product Identification =====

Product ID:FOG OIL

MSDS Date:01/01/1987

FSC:9150

NIIN:00-261-7895

MSDS Number: BDPNS

=== Responsible Party ===

Company Name:CALUMET REFINING CO DIV OF CALUMENT INDUSTRIES INC

Address:HC 62

Box:460

City:PRINCETON

State:LA

ZIP:71067

Country:US

Info Phone Num:318-949-2421

Emergency Ph

one Num:318-949-2421

CAGE:69487

=== Contractor Identification ===

Company Name:CALUMET REFINING CO DIV OF CALUMENT INDUSTRIES INC

Address:HC 62

Box:460

City:PRINCETON

State:LA

ZIP:71067

Country:US

Phone:318-949-2421

CAGE:69487

===== Composition/Information on Ingredients =====

Ingred Name:LUBRICATING OIL(PETROLEUM) TAKE TLV AS OIL MIST=5MG/CUM

Fraction by Wt: 100%

ACGIH TLV:5MG/CUM(OILMIST

===== Hazards Identification =====

Effects of Overe

xposure:LOW ORDER OF TOXICITY.CONTACT MAY CAUSE IRRITATION TO SKIN AND EYES.

=====  
=====  
First Aid Measures  
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H\*2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

=====  
=====  
Fire Fighting Measures  
=====

Flash Point:300F/150C(C.O.C)

Lower Limits:U/K

Upper Lim

its:U/K

Extinguishing Media:FOAM,DRY CHEMICAL,CO\*2,WATER FOG/SPRAY

Fire Fighting Procedures:USE WATER SPRAY TO COOL CONTRS.USE SCBA IN FIRES AND CONFIND

Unusual Fire/Explosion Hazard:DO NOT HEAT AT DECOMPOSITION TEMP;COMBUSTION PRODUCT:FUMES,CO AND CO\*2

=====  
=====  
Accidental Release Measures  
=====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION.REMOVE SPARKS,FLAMES AND HOT SURFACES.USE SUITABLE ABSORBENTS AND RECOVER FOR PROPER DISPOSAL.

=====

=====  
=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA.KEEP AWAY FROM HEAT,OPEN FLAMES,STRONG OXIDANTS.AVOID TEMP.ABOVE 120F.

Other Precautions:AVOID PROLONG CONTACT OF SKIN AND EYES.WASH THOROUGHLY AFTER EACH HANDLING.DO NOT USE CONTAMINATED CLOTHES.

=====  
=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR OIL MIST.

Ventilation:

PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN