View NSN Online: https://aerobasegroup.com/nsn/9150-00-261-8144 VINELAND WAX SPECIALTIES, INC. -- CUTTING FLUID VV-C-846A, TYPE I -- 9150-00-261-8144 Product ID: CUTTING FLUID VV-C-846A, TYPE I MSDS Date:01/01/1987 FSC:9150 NIIN:00-261-8144 MSDS Number: BDPPP === Responsible Party === Company Name: VINELAND WAX SPECIALTIES, INC. Emergency Phone Num:(609)697-3152 CAGE:63400 === Contractor Identification === Company Name: VINELAND **CHEMICAL CO** Address: W WHEAT RD Box:City:VINELAND State:NJ ZIP:08360 Country:US CAGE:7D159 Company Name: VINELAND WAX SPECIALTIES INC WAX PROCESSING Address: S RAILROAD BLVD Box:City:MINOTOLA State:NJ ZIP:08341 Country:US Phone: 609-697-3941 (OUT OF BUSINESS) CAGE:63400 ======= Composition/Information on Ingredients ========

Ingred Name: HYDROTREATED NAPHTENIC WITH EMULSIFIER

=========== Hazards Identification ==========

ACGIH TLV:5MG/CUM (MIST)

Ingred Name: ADDITIVES

Effects of Overexposure:DIZZINESS,HEADACHES.
======================================
First Aid:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. SKIN:WASH WITH SOAP & WATER. EYES:FLUSH WITH WATER 15 MIN. KEEP WARM AND QUIET CALL PHYSICIAN.
=========== Fire Fighting Measures ===========
Flash Point:325F,163C,COC Lower Limits:0.9 Upper Limits:7.0 Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG. Fire Fighting Procedures:COOL DOW N HEATED CONTAINERS W.WATER. Unusual Fire/Explosion Hazard:AVOID OVERHEATED CLOSED CONTAINERS WHICH INCREASES PRESSURE.
======== Accidental Release Measures ==========
Spill Release Procedures:REMOVE IGNITION SOURCES,VENTILATE AREA WELL.ABSORB WITH VERMICULITE OR OTHER MATERIALS, SUCH AS SAWDUST,RAGS,PAPER & PLACE IN CLOSED CONTAINER. USE NON SPARKING TOOLS. WEAR PROPER PROTECTIVE EQUIPMENT DURING CLEAN UP.
======================================
Handling and Storage Precautions:STORE IN COOL,DRY WELL VENTED LOW FIRE RISK AREA. PROTECT FROM HEAT,SHOCK,FRICTION. KEEP CONTAINERS CLOSED. Other Precautions:WASH SKIN AFTER HANDLING PRODUCT.USE SOAP AND WATERDO NOT STORE PRODUCT NEAR OXIDANTNO SMOKING NEAR PRODUCT
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NIOSH APPVD.RESP.IF TLV EXCEEDED Ventilation:LOCAL EXHAUST TO ELIMINATE MISTS/FUMES/GASES. (60FPM HOOD

=====

HCC:V6
Boiling Pt:B.P. Text:550F,288C
Vapor Pres:5.
Spec Gravity:0.91
Evaporation Rate & Description Reference: