

HARSHAW/FILTROL PARTNERSHIP -- FILTROL CLAY PRODUCT DESICCITE 25#00008. --
6850-00-264-6573

=====
===== Product Identification =====

Product ID:FILTROL CLAY PRODUCT DESICCITE 25#00008.

MSDS Date:09/05/1984

FSC:6850

NIIN:00-264-6573

MSDS Number: BDQQJ

=== Responsible Party ===

Company Name:HARSHAW/FILTROL PARTNERSHIP

Address:30100 CHAGRIN BLVD

City:CLEVELAND

State:OH

ZIP:44124-5705

Country:US

Info Phone

Num:216-292-9200

Emergency Phone Num:216-292-9200

CAGE:8Z371

=== Contractor Identification ===

Company Name:HARSHAW/FILTROL PARTNERSHIP

Address:30100 CHAGRIN BLVD

Box:City:CLEVELAND

State:OH

ZIP:44124-5705

Country:US

Phone:216-349-7300

CAGE:8Z371

=====
===== Composition/Information on Ingredients =====

Ingred Name:SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: 3.0%

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:MONTMORILLONITE CLAY

CAS:12199-37-0

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:UNKNOWN Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN AND
RESPIRATORY TRACT,POSSIBLE LONGS DISEASE. CHRONIC:PROGRESSIVE
PULMONARY FIBROSIS DUE TO FREE SILICA.
Effects of Overexposure:INHAL: TLV MAY PRODUCE PNEUMOCONIOSIS IN
SUSCEPTIBLE; SKIN: REPEATED CONTACT CAN DRY THE SKIN.
Medical Cond Aggravated by Exposure:IMPAIRMENT OF PUL
MONARY FUNCTION

=====
===== First Aid Measures =====

First Aid:USE NORMAL FIRST AID PROCEDURES, CALL A PHYSICIAN IF NEEDED.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION; VACUUM AND
COLLECT FOR PROPER DISPOSAL.

=====
===== Handling and Storage ==
=====

Handling and Storage Precautions:NONE
Other Precautions:AVOID CONTACT WITH SKIN AND EYES. DO NOT BREATHE
DUST.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR SILICA
DUST IF ABOVE TLV/PEL.
Ventilation:LOCAL/GENERAL TO CONTROL DUST
Protective Gloves:TYPE AS REQD
Eye Protection:SAFETY GLASSES
Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.
Work Hygienic Practices:A

VOID CONTACT WITH SKIN AND EYES;DO NOT BREATHE
DUST.

Supplemental Safety and Health
MSDS RECEIVED BY DGSC-SLM:23FEB,1988

===== Physical/Chemical Properties =====

HCC:N1
Melt/Freeze Pt:=-593.3C, #####F
Spec Gravity:2.0
Solubility in Water:NEGLIGIBLE
Appearance and Odor:CREAM TO WHITE COLORED POWDER;ODORLESS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE
Stability Condition to Avoid:NONE
Hazard
ous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHALL BE I/A/W ALL FEDERAL, STATE, OR
LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all li
ability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.