

DAVIS HOWLAND OIL CORP. -- VV-C-846-A TYPE I;CUTTING FLUID -- 9150-00-265-9405
===== Product Identification =====

Product ID:VV-C-846-A TYPE I;CUTTING FLUID

MSDS Date:01/01/1987

FSC:9150

NIIN:00-265-9405

MSDS Number: BDRFC

=== Responsible Party ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Info Phone Num:716-473-6650

Emergency Phon

e Num:716-473-6650

CAGE:5A565

=== Contractor Identification ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

===== Composition/Information on Ingredients =====

Ingred Name:CUTTING FLUID (CONSISTING OF MINERAL OIL AN EMULSIFIER)

Fraction by Wt: >99%

Other REC Limits:5MG/CUM AS OIL MIST

===== Hazards Identification =====

Routes of Entry: Inhalation:YE

S Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:SLIGHT IRRITATION OF EYES AND
SKIN CHRONIC:NOT KNOWN;MAY CAUSE DERMATITIS.
Explanation of Carcinogenicity:SEE SUPPLEMENTAL DATA
Effects of Overexposure:MAY CAUSE SLIGHT IRRITATION OF SKIN OR EYES
AFTER PROLONGED AND REPEATED CONTACT.
Medical Cond Aggravated by Exposure:NOT KNOWN

=====
===== First Aid Measures =====

First Aid:INHALE:REMOVE
TO FRESH AIR, GIVE CPR/O*2 IF
NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:320F/160C
Extinguishing Media:CO*2, DRY CHEMICALS, SAND, EARTH, AND FOAM.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA; AVOID BREATHING
FUMES.
Unusual Fire/Explosion Hazard:NONE NOTED

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION; ABSORB ON
POROUS MATERIAL AND TRANSFER TO A CONTAINER FOR PROPER DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID FREEZING; KEEP CONTAINER CLOSED
WHEN NOT IN USE.
Other Precautions:AVOID CONTACT WITH SKIN AND EYES. DO NOT INHALE
VAPORS/MIST.

=====
===== Exposure Controls/Personal Prote

ction =====

Respiratory Protection:NO SPECIAL REQMENTS UNDER ORDINARY
CONDITIONS/ADEQUATE VENT.

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE
VENTILATION

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE
WASH STATION

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

IN LETTER DATED 14NOV89 1 LT J.A.HEWITT, 316 AIR DIV CLINIC REPORTED
125

PPM PCB IN THIS PRODUCT. L.KLIPPER. DAVIS-HOWLAND, CLAIMS NO
PCBS, HMIS INVESTIGATING. * IN MAR92 THE ABOVE QUESTIONED. NO TRAC
E OF THE CLAIM COULD BE FOUND. ALL RETURNS WERE FOR EXPIRED SHELF
LIFE. NO CASE HISTORY FOUND AT DGSC-SSH. DISREGARD!!!

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>500F/260C

Spec Gravity:0.908

Solubility in Water:100% (COMPLETE)

Appearance and Odor:BROWN FLUID-MILD ODOR

===== Stability a
nd Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE NOTED

Stability Condition to Avoid:HEAT

Hazardous Decomposition Products:CARBON MONOXIDE,CARBON
DIOXIDE,INCOMPLETELY BURNED CARBON PRODUCTS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH
LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This info

Information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.