View NSN Online: https://aerobasegroup.com/nsn/8040-00-266-0837

Product ID:SPHINXPASTE D-3603 MSDS Date:01/01/1987 FSC:8040 NIIN:00-266-0837 **MSDS Number: BDRGK** === Responsible Party === **Company Name: BORDEN INC** Emergency Phone Num:614-457-5200 CAGE:07982 === Contractor Identification === Company Name: ARABOL DEPT BORDEN CHEMICAL DIV OF BORDEN INC Address:180 E BROAD ST Box:C ity:COLUMBUS State:OH ZIP:43215-3705 Country:US Phone:614-225-6124 CAGE:84163 **Company Name: BORDEN INC** Address:180 E BROAD ST Box:208 City:COLUMBUS State:OH ZIP:43215-3705 Country:US Phone:614-225-6124 CAGE:07982

Ingred Name:STARCH CAS:9005-25-8 RTECS #:GM5090000 OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3; 9192

Ingred Name:CALCIUM CHLORIDE CAS# 10043-52-4 1-10% CAS:10043-52-4 RTECS #:EV9800000

Effects of Overexposure:SKIN:MAY IRRIT ON PRLG RPTD CONTACT.INGEST:NOT HARMFUL W/ NORM USE.EYE:IRRIT.SKIN ABSORB;NO HAZ.SUPP

First Aid:INGEST:GIVE TWO GLASS OF WATER & INDUCE VOMIT,ONLY IF CONSCIOUS.CALL MD.INHAL;REMOVE TO FRESH AIR.IF NO BREATH,GIVE CPR.PHONE MD.IF BREATH DIFFICULT,GIVE O*2.EYE:IMMED FLUSH W/ WATER FOR AT LEAST 15 M IN.CALL MD.SKIN:IN CA SE OF IRRIT,FLUSH W/ WATER.

Extinguishing Media:WATER SPRAY,DRY CHEM,FOAM,CO*2. Fire Fighting Procedures:USE WATER TO COOL EXPOSED CONTAINERS. Unusual Fire/Explosion Hazard:WILL NOT BURN UNLESS WATER HAS EVAPORATED.

Spill Release Procedures:LARGE QUANTITIES:ENCLOSE W/ DIKING MATRL TO PREVENT SEEPAGE INTO NATURAL BODIES OF WATER,THEN CONSULT BORDEN

CHEMICAL.SMALL QUANTITIES:SOAK UP W/ ABSORBENT MATERIAL AND REMOVE TO A CHEMICAL DISPOSAL A REA.

Handling and Storage Precautions:INHAL:AVOID BREATHING VAPOR.USE W/ ADEQUATE VENTILATION.SKIN:AVOID PRLG/RPTD CONTACT.EYE:AVOID CONTACT.WASH THOROUGHLY AFTER HANDLING.DO NOT FREEZE.
Other Precautions:HANDLE IN ACCORDANCE W/ GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICES.THESE PRACTICES INCLUDE AVOIDING UNNECESSARY EXPOSURE AND REMOVAL OF THE MATERIAL FROM EYES,SKIN & CLOTH.UNUSABLE AFTER FRZ

====== Exposure Controls/Personal Protection ==========

Respiratory Protection:USE NIOSH/MSHA APPRVD EQUIP.SELECT BY THE FORM & CONC OF CONTAMINANT Ventilation:LOCAL EXHST TO KEEP CONC BELOW TLVS FOR CONTAMINANTS Protective Gloves:IMPERVIOUS Eye Protection:N/R(PER MFR). Supplemental Safety and Health MSDS PREP:86276.EFFECT OF OVEREXP:INHAL:MAY BE HARMFUL.LIQ OR VAP CAN IRRIT RESPIR TRACT.

TLV:DUST:10MG/CUM TOTAL;5MG/CUM RESPIRABLE.STORE IN A COOL,DRY PLACE.STORAGE LIFE @ 70F:6 MONTH.

HCC:N1 Boiling Pt:B.P. Text:212F,100C Spec Gravity:1.13 Solubility in Water:SOLUBLE Appearance and Odor:MILKY WHITE PASTE,BLAND ODOR.

Stability Indicator/Materials to Avoid:YES NONE(PER CALL TO MFR) Stability Condition to Avoid:N/K(PER MFR) Hazardous Decompo sition Products:OXIDES OF CARBON.

Waste Disposal Methods:RECOVER FREE LIQUID.ABSORB RESIDUE AND DISPOSE OF ACCORDANCE W/ LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be ac curate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.