

AMCHEM PRODUCTS,INC. - FOSTER DIV -- FOSTER SPARK-FAS ADHESIVE 85-20,MIL-A-3316 --
8040-00-273-8710

===== Product Identification =====

Product ID:FOSTER SPARK-FAS ADHESIVE 85-20,MIL-A-3316

MSDS Date:01/01/1985

FSC:8040

NIIN:00-273-8710

MSDS Number: BDSCK

=== Responsible Party ===

Company Name:AMCHEM PRODUCTS,INC. - FOSTER DIV

Address:300 BROOKSIDE AVE

City:AMBLER

State:PA

ZIP:19002-3436

Country:US

CAGE:DO024

=== Contractor Identification ===

Company Name:AMCHEM PRODUCTS,INC.

Address:300 BROOKSIDE AVE

City:AMBLER

Phone:313-583-9300

CAGE:DO024

Company Name:PARKER-AMCHEM/HENKEL CORPORATION

Address:32100 STEPHENSON HIGHWAY

Box:City:MADISON HEIGHTS

State:MI

ZIP:48071

Country:US

Phone:1-517-263-9430 CHEM EMER18004249300

CAGE:84063

===== Composition/Information on Ingredients =====

Ingred Name:METHYLENE CHLORIDE (SARA III)

CAS:75-09-2

RTECS #:PA8050000

Fraction by Wt: 58%

OS

HA PEL:500 PPM/C,1000; Z2
ACGIH TLV:50 PPM, A2; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 6%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:CHLORINATED WAX
Fraction by Wt: 13%

=====
Hazards Identification
=====

Effects of Overexposure:NAUSEA,HEADACHE,DEFATTING OF SKIN.

=====
First Aid Measures
=====

First Aid:VENTILATION,FRESH AIR.

=====
Fire Fighting Measures
=====

Flash Point:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:COVER WITH GREASE ABSORBENT,PROVIDE
VENTILATION TO EXHAUST SOLVENT VAPORS AND CLEAN UP WITH
NON-FLAMMABLE SOLVENTS.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN

USE.AVOID PROLONGED BREATHING OF VAPOR AND SKIN CONTACT.DO NOT TAKE INTERNALLY.

Other Precautions:VAPORS HARMFUL - USE ONLY WITH ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN.

Ventilation:LOCAL EXHAUST/MECHANICAL AIR DILUTION.

Protective Gloves:SOLVENT RESIST=

Supplemental Safety and Health

CLASS 2 PRODUCT,PKG: 1 GAL

===== Physical/Chemical

I Properties =====

HCC:T4

Spec Gravity:1.3

Solubility in Water:IMMISCIBLE

Appearance and Odor:OFF-WHITE VISCOUS LIQUID,CHLORINATED SOLVENT ODOR

Percent Volatiles by Volume:68

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:ON PYROLYSIS - HCL

===== Disposal Considerations =====

Waste Disposal Methods:COMPLY WITH LOCAL,STATE AND FEDERAL REGULATIONS.

D

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation

