

FEDERAL SPECIFICATIONS, PROMULGATED BY GSA -- MMM-A-121 -- 8040-00-273-8717
===== Product Identification =====

Product ID:MMM-A-121
MSDS Date:01/01/1987
FSC:8040
NIIN:00-273-8717
MSDS Number: BDSDB
=== Responsible Party ===
Company Name:FEDERAL SPECIFICATIONS, PROMULGATED BY GSA
City:WASHINGTON
State:DC
Country:US
Emergency Phone Num:201-694-0845
CAGE:81348
=== Contractor Identification ===
Compan
y Name:FEDERAL SPECIFICATIONS, PROMULGATED BY GSA
Box:City:WASHINGTON
State:DC
Country:US
CAGE:81348

===== Composition/Information on Ingredients =====

Ingred Name:METALLIC OXIDES
Fraction by Wt: 1%

Ingred Name:VEHICLE
Fraction by Wt: 11%

Ingred Name:SOLVENTS
Fraction by Wt: 82%

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 17%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM; Z-2
ACGIH TLV:S, 50 PPM; 9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty

:1000 LBS

Ingred Name:HEXANE (N-HEXANE)

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 50%

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====
===== Hazards Identification =====

Effects of Overexposure:NARCOSIS AND/OR POSSIBLE HEADACHE OR BRONCHIAL CATARRH

=====
===== First Aid Measures =====

First Aid:FRESH AIR- SEE DR.

=====
===== Fire Fighting Measures =====

Flash Poi

nt:15 F TCC -9C

Lower Limits:1.2

Upper Limits:13

Extinguishing Media:DRY CHEMICAL, CO*2, FOAM, TRICHORETHANE

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN

Unusual Fire/Explosion Hazard:KEEP AWAY FROM OPEN FLAME,SPARKS,HOT SURFACES AND OXIDIZERS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE NEAR OR IN DIRECT SUNLIGHT. STORE IN SOLVENT STORAGE AREA.

=====
===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST

Protective Gloves:YES

Eye Protection:SAFETY GLASSES

Other Protective Equipment:HAND CREAM

Supplemental Safety and Health

ACETONE AL3150000,23% TLV 1000 PPM; MEK OS0175000 10% TLV 200 PPM

PHENOLIC RESIN 6%

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:132 F 56 C

Vapor Pres:185

Vapor

Density:0.75

Spec Gravity:0.8

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:OFF WHITE,KETONE AND NAPHTHA ODOR

Percent Volatiles by Volume:88

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:HCL, PHENOL,CO, CO*2,AMMONIA, CHLORINE
GAS

===== Disposal Considerations =====

Waste Disposal Methods:SOLVENT DISPOSAL PROCEDURES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.