

REICHOLD CHEMICALS, INC (STERLING DIVISION) -- 80-394 ELECTR.INSULATING VARNISH T-394A  
-- 5970-00-285-0271

===== Product Identification =====

Product ID:80-394 ELECTR.INSULATING VARNISH T-394A

MSDS Date:09/01/1986

FSC:5970

NIIN:00-285-0271

MSDS Number: BDTLB

=== Responsible Party ===

Company Name:REICHOLD CHEMICALS, INC (STERLING DIVISION)

Address:9 OHIO RIVER BLVD

City:SEWICKLEY

State:PA

ZIP:1514

3

Country:US

Info Phone Num:(412)766-7600

Emergency Phone Num:(800)423-3003(EXCEPT NY)SEE SUPPL.

CAGE:3A684

=== Contractor Identification ===

Company Name:NU-BRITE CHEMICAL CO INC, STERLING GROUP

Address:NINE OHIO RIVER BLVD

Box:City:SEWICKLEY

State:PA

ZIP:15143-2199

Country:US

Phone:CHEMTREC 800-424-9300

CAGE:78580

Company Name:REICHOLD CHEMICAL INC

Address:525 N BROADWAY

Box:13582

City:WHITE PLAINS

State:NY

ZIP:10603-3216

Country:US

CAGE:3A684

===== Composition/Information on Ingredi

ents =====

Ingred Name:MODIFIED PHENOLIC RESIN  
Fraction by Wt: 30-60%

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 30-60%  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)  
CAS:67-63-0  
RTECS #:NT8050000  
Fraction by Wt: 10-30%  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:SOLICYLANILIDE AS FUNCIDE (TAKEN FROM PREVIOUS HM  
IS)  
Fraction by Wt: 10%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:ACUTE: EYES:IRRITATION;  
SKIN:IRRITATION OR RASH; INHALATION:IRRITATION OF  
EYES,NOSE,THROAT,HEADACHE,NAUSEA,VOMIT. CHRONIC:PROLONGED OR  
REPEATED CONTACT WITH SKIN MAY CAUSE DERMATITIS.DEFEATTING TO SKI  
N.

Effects of Overexposure:SEE HEALTH HAZARDS  
Medical Cond Aggravated by Exposure:NONE NOTED.

===

===== First Aid Measures =====

First Aid:EYES:FLUSH W.WTR FOR 15 MIN.CALL PHYSICIAN;SKIN:WASH W.SOAP &  
WTR AT ONCE;INHALATION:REMOVE TO WELL VENTILATED AREA.IF DIFFICULTY  
IN BREATHING GIVE CPR/O\*2.GET MEDICAL ATTENTION AT  
ONCE;INGESTION:DO NOT INDUCE VOMIT.CALL PHYSICIAN AT  
ONCE.ASPIRATION OF MATERIAL INTO LUNGS DUE TO VOMITING CAN CAUSE  
CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

===== Fire Fighting Measures =====

=====

Flash Point Method:SCC

Flash Point:42F,5.6C

Lower Limits:2.5

Extinguishing Media:CO\*2, FOAM, DRY CHEM & H\*2O FOG.

Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY RUPTURE OR EXPLODE  
WHEN HEATED.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES,VENTILATE AREA  
WELL.ABSORB WITH VERMICULITE OR OTHER MATERIALS, SUCH AS  
SAWDUST,RAGS,PAPER & PLACE IN CLOSED CO  
NTAINER. USE NON SPARKING  
TOOLS. WEAR PROPER PROTECTIVE EQUIPMENT DURING CLEAN UP.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED OR REPEATED INHALATION  
OF SPRAY MISTS AND HEATED VAPORS.AVOID ALL SKIN CONTACT.USE  
ADEQUATE VENTILATION.AVOID WARM STORAGE&ING.SOURCES  
Other Precautions:HANDLE AS A FLAMMABLE LIQUID. CONSULT PRODUCT  
BULLETIN PRIOR TO USING THIS MATERIAL.

===== Exposure Controls/Personal  
Protection =====

Respiratory Protection:NIOSH APPROVED RESPIRATOR SHOULD BE WORN TO  
AVOID BREATHING SPRAY MISTS,HEATED VAPORS OR IF TLV IS EXCEEDED.

Ventilation:LOCAL EXHAUST AND GENERAL VENTILATION RECOMMENDED

Protective Gloves:CHEM.RESISTANT PLASTIC OR RUBBER

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT. SAFETY  
SHOWER AND EYEWASH FOUNTAIN.

Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE  
EATING,SMOKING,USING TOILET FAC  
ILITIES.

Supplemental Safety and Health

N.Y. ONLY EMERG.PHONE:(800)442-4844/MFR REPORTED BOIL  
PT,VAP.PRESS,VAP.DENS AND EVAP RATE OF ISOPROPANOL.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:180F,82C

Vapor Pres:35

Vapor Density:2.0

Spec Gravity:0.94

Evaporation Rate & Reference:2.83 (BU AC=1)

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER LIQUID-PUNGENT ODOR.

Percent Volatiles by Volume:48

===== Stability and Re

activity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: WARM STORAGE AND IGNITION SOURCES.

Hazardous Decomposition Products: CO, CO\*2, OXIDES OF NITROGEN

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF  
IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL, STATE & FEDERAL  
REGULATIONS.

Disclaimer (provided with this information  
by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.