

ELDORADO CHEMICAL CO., INC. -- ELDORADO ED-371 -- 6850-00-285-6056

=====
Product Identification
=====

Product ID:ELDORADO ED-371

MSDS Date:08/04/1986

FSC:6850

NIIN:00-285-6056

MSDS Number: BDTRG

=== Responsible Party ===

Company Name:ELDORADO CHEMICAL CO., INC.

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State:TX

ZIP:78265

Country:US

Info Phone Num:512-653-9323

Emergency Phone Num:512-65

3-9323

Preparer's Name:PAT E.SMITH

CAGE:55208

=== Contractor Identification ===

Company Name:ELDORADO CHEMICAL COMPANY, INC.

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State:TX

ZIP:78265-4837

Country:US

Phone:800-531-1088/ 210-653-2060

CAGE:55208

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHANOLAMINE

CAS:141-43-5

RTECS #:KJ5775000

Fraction by Wt: 5.0%

OSHA PEL:3 PPM/6 STEL

ACGIH TLV:3 PPM/6 STEL; 9192

Ingred Name:CRESOL, ALL ISOMERS (CRESYLIC

ACID) (SARA III)
CAS:1319-77-3
RTECS #:GO5950000
Fraction by Wt: 17.0%
OSHA PEL:S, 5 PPM
ACGIH TLV:S, 5 PPM; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:2-BUTOXYETHANOL
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 3.0%
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293

Ingred Name:AROMATIC HIGH FLASH NAPHTHA
CAS:64742-95-6
Fraction by Wt: 65.0%
Other REC Limits:100 PPM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES
Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:CORROSIVE TO SKIN AND
EYES;RESPIRATORY OR G.I.TRACT IRRITATION.
Effects of Overexposure:INH: NAUSEA; SKIN: DEFATTING/AMINE-RASH; EYES:
IRRITATION.
Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====
First Aid Measures
=====

First Aid:INH:REMOVE TO FRESH AIR. SKIN:WASH W/SOAP & WATER. EYES:FLUSH
W/ WATER FOR 15 MIN, SEE MD.

=====
Fire Fighting Measures
=====

Flash Point:270F/132C
Autoignition Temp:Autoignition Temp Text:850F
Lower Limits:2.0
Upper Limits:15.0
Extinguishing Media:CO*2, FOAM
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:TAKE UP W/ OIL ABSORBENT MATERIAL & BURY IN
SANITARY LANDFILL. SMALL AMOUNTS MAY BE FLUSHED TO SEWAGE SYSTEM
W/WATER.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NOT REQUIRED (MFR)
Ventilation:LOCAL EXHAUST-200 CFM TO KEEP BELOW TLV.
Protective Gloves:RUBBER
Eye Protection:FACE SHIELD
Other Protective Equipment:RUBBER APRONS & BOOTS.
Supplemental Safety and Health
OTHER EMERGENCY PHONE: 512-494-5337. SPEC:TYPE II. CONTAINER:5 GAL CAN.

===== Physical/Chemical Properties =====

HCC:B2
Boiling Pt:=104.4C, 220.F
Vapor Pres:20MM HG
Spec Gravity:1.0
Evaporation Rate & Reference:1.0 (WATER=1)
Solubility in
Water:EMULSIFIES
Appearance and Odor:THIN AMBER LIQUID;CRESOL ODOR
Percent Volatiles by Volume:60

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECOMMENDS: TREATING MATERIAL TO REMOVE
NON-VOLATILE HYDROCARBONS & PHENOLICS; FLUSH REMAINDER TO SEWAGE
SYSTEM. DISPOSAL METHOD MUST BE IAW
FEDERAL, STATE & LOCAL CODES.

===== MSDS Transport Information =====

Transport Information:PSN PER MSDS. HCC ASSIGNED TO CORRESPOND WITH
PSN.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this infor

mation to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.