

CON-LUX COATINGS,INC. -- ENAMEL,DECK,INTERIOR,DARK GREEN -- 8010-00-286-3986

===== Product Identification =====

Product ID:ENAMEL,DECK,INTERIOR,DARK GREEN

MSDS Date:01/01/1985

FSC:8010

NIIN:00-286-3986

MSDS Number: BDTVP

=== Responsible Party ===

Company Name:CON-LUX COATINGS,INC.

Emergency Phone Num:201-287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

===== Composition/Information on Ingredients =====

Ingredient Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 25%

OSHA PEL:100 PPM

Ingredient Name:ZINC CHROMATE

CAS:13530-65-9

RTECS #:GB3290000

Fraction by Wt: 7%

OSHA PEL:0.1 MG/M3 (CRO3)

ACGIH TLV:0.01MG/M3(CR)A1;9192

Ingredient Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS

#:SE7555000
Fraction by Wt: 5%
OSHA PEL:100 PPM

===== Hazards Identification =====

Effects of Overexposure:IRRITATION OF EYES AND SKIN. IRRITATION OF
RESPIRATORY TRACT HEADACHE OR DIZZY.

===== First Aid Measures =====

First Aid:EYES/SKIN:FLUSH W/PLENTY OF WATER. INHAL:REMOVE TO FRESH AIR.
CALL DR IF IRRITATION PERSISTS.

===== Fire Fighting Measures =====

Flash Point:41/105 CC

L

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:USE CLASS B EXTINGUISHERS(CARBON DIOXIDE,DRY
CHEM.,FOAM)

Fire Fighting Procedures:USE WATER TO COOL CLOSED CONTAINERS & PREVENT
AUTOIGNITION

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED AND
ISOLATE FROM SOURCES OF IGNITION

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES,HOT
SURFACES,ELECTRICAL,STATIC OR FRICTIONAL SPARKS)ABOID B
REATHING
BAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SPARKING
TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED
TEMPERATURES.KEEP AWAY FROM OPEN FLAMES AND SPARKS.

Other Precautions:DO NOT TAKE INTERNALLY.CONTAINERS SHOULD BE GROUNDED
WHEN POURING.AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protecti

on:BUREAU OF MINES APPROVED CHEM/MECH FILTER
RESPIRATOR

Ventilation:LOCAL EXHAUST

Protective Gloves:YES

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH
CONTAMINATED CLOTHING

Supplemental Safety and Health

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.DO NOT APPLY
TO HOT SURFACES.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:149/300

Vapor Pres:2

Vapor Density:4.5

Spec Gravity:1.29

Evaporation Rate & Reference:BUAC = 1: 0.15

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GREEN LIQUID,MILD AROMATIC ODOR.

Percent Volatiles by Volume:48

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO, CO*2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE,AND
FEDERAL REGULATIONS.D

O NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this inf

ormation to their
particular situation.