

THE LOCKREY CO. INC. -- LIQUI MOLY NV THREAD COMPOUND -- 8030-00-286-5453
===== Product Identification =====

Product ID:LIQUI MOLY NV THREAD COMPOUND
MSDS Date:01/01/1985
FSC:8030
NIIN:00-286-5453
MSDS Number: BDTVZ
=== Responsible Party ===
Company Name:THE LOCKREY CO. INC.
Emergency Phone Num:609-665-4794
CAGE:KO338
=== Contractor Identification ===
Company Name:LOCKREY CO LUBRICANTS DIVISION
A
Address:CEDAR SHORES
Box:City:SOUTHAMPTON
State:NY
ZIP:11968
Country:US
CAGE:98113
Company Name:THE LOCKREY CO. INC.
CAGE:KO338

===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE GLYCOL (SARA III)
CAS:107-21-1
RTECS #:KW2975000
OSHA PEL:C 50 PPM
ACGIH TLV:C 50 PPM,VAPOR; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:MOLYBDENUM DISULFIDE
CAS:1317-33-5
RTECS #:QA4697000
OSHA PEL:10 MG/M3 TDUST (MO)
ACGIH TLV:10 MG/M3 (MO); 8990

=====

Hazards Identification =====

Effects of Overexposure:NONE

===== First Aid Measures =====

First Aid:EYES,SKIN: FLUSH W/ WATER FOR AT LEAST 15 MINUTES.

===== Fire Fighting Measures =====

Flash Point:470F, 243.3,(OC)

Extinguishing Media:CO*2, DRY CHEMICAL, FOAM

Fire Fighting Procedures:SELF-CONTAIN BREATH APP

Unusual Fire/Explosion Hazard:BURNING CAN PRODUCE OXIDES OF NITROGEN, SULFUR, & CO*2.

=====

===== Accidental Release Measures =====

Spill Release Procedures:COLLECT FOR DISPOSAL

===== Handling and Storage =====

Handling and Storage Precautions:NONE

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:MFR RECOMMENDS NONE

Ventilation:LOCAL EXHAUST

Protective Gloves:PLASTIC

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYE & SAFETY SHOWER

Supplemental Safe

ty and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:482F, 250C

Vapor Density:1

Spec Gravity:0.999

Evaporation Rate & Reference:NEGLIGIBLE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLUISH GRAY;SWEET,PLEASANT ODOR.

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

CONTACT WITH CHEMICAL OXIDANTS SHOULD BE AVOIDED.

Stability Condition t

o Avoid:ABNORMAL CONDITIONS PRODUCE INSTABILITY.
Hazardous Decomposition Products:BURNING CAN PRODUCE OXIDES OF
NITROGEN, SULFUR, CO*2.

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECOMMENDS INCINERATION. WASTE DISPOSAL
METHOD MUST BE IAW FEDERAL, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.