

CORONADO PAINT CO INC.308 OLD COUNTRY EDGEWATER FL -- WHITE -- 8010-00-290-4050

=====
Product Identification
=====

Product ID:WHITE

MSDS Date:01/01/1987

FSC:8010

NIIN:00-290-4050

MSDS Number: BDVDN

=== Responsible Party ===

Company Name:CORONADO PAINT CO INC.308 OLD COUNTRY EDGEWATER FL

Emergency Phone Num:904-428-6461

CAGE:33200

=== Contractor Identification ===

Company Name:CORONADO PAINT COMPAN
Y, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812

Country:US

Phone:904-428-6461

CAGE:33200

=====
Composition/Information on Ingredients
=====

Ingred Name:ALKYD RESIN

Fraction by Wt: 30.0%

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS:8002-05-9

RTECS #:SE7449000

Fraction by Wt: 19.0%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 8990

=====
Hazards Identification
=====

Effects of Overexposure:PRODUCES S

EVERE IRRITATION DRYING OF SKIN
EXCESSIVE INHALATION CAUSES HEADACHE,DIZZINESS,NAUSEA.

=====
First Aid Measures
=====

First Aid:EYE CONTACT FLUSH W/WATER,SKIN CONTACT WASH W/MILD SOAP &
WATER & APPLY SKIN CREAM. INHALATION REMOVE TO FRESH AIR.AND CALL
MD. APPLY ARTIFICIAL RESPIRATION,IF NECESSARY.

=====
Fire Fighting Measures
=====

Flash Point:102F SETA
Lower Limits:0.8
Upper Limits:5.0
Extinguishing Media:FO
AM CARBON DIOXIDE DRY CHEMICAL.
Fire Fighting Procedures:TREAT AS CLASS B FIRE
Unusual Fire/Explosion Hazard:VAPOR MAY EXPLODE WHEN MIX WITH AIR

=====
Accidental Release Measures
=====

Spill Release Procedures:WEAR A RESPIRATOR FLUSH W/WATER INTO-RETAINING
AREA OR CONTAINER. AVOID EXPOSURE TO SPARKS,FIRE OR HOT METAL
SURFACE.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS,OPEN
FLAME.USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED
SKIN CONTACT.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:SELF CONTAINED NIOSH APPROVED RESPIRATOR IF
NECESSARY.
Ventilation:KEEP AWAY FROM HEAT
Protective Gloves:NIOSH APPROVED
Eye Protection:CHEMICAL GOGGLES
Other Protective Equipment:EYE BATH & SAFETY SHOWER.
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F4
B

Boiling Pt: B.P. Text: 315 F 157 C

Vapor Pres: 80

Vapor Density: 4.9

Spec Gravity: 0.913

Evaporation Rate & Reference: SLOWER THAN NBUACT

Solubility in Water: INSOLUBLE

Appearance and Odor: PETROLEUM DISTILLATE ODOR WHITE ORANGE LIQUID

Percent Volatiles by Volume: 64.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZERS.

Stability Condition to Avoid: EXCESSIVE HEAT, SPARK, OPEN FLAMES.

Hazardous Decomposition Products: THERMAL D

ECOMPOSITION MAY YIELD CARBON

MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: LANDFILL, INCINERATION UNDER SAFE SUPERVISED
CONDITIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability

for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.