

GETTY REFINING AND MARKETING CO -- SKELLYSOLVE-S-66, TYI GRADE A -- 8010-00-290-4079

=====
Product Identification
=====

Product ID:SKELLYSOLVE-S-66, TYI GRADE A

MSDS Date:01/01/1985

FSC:8010

NIIN:00-290-4079

MSDS Number: BDVDW

=== Responsible Party ===

Company Name:GETTY REFINING AND MARKETING CO

Address:1437 S BOULDER

Box:1650

City:TULSA

State:OK

ZIP:74102

Country:US

Info Phone Num:918-749-9800

Emergency Phone Num:918-749-9800

CAGE:87905

=== Contractor Identification ===

Company Name:GETTY REFINING AND MARKETING CO

Address:1437 S BOULDER

Box:1650

City:TULSA

State:OK

ZIP:74102

Country:US

Phone:918-749-9800

CAGE:87905

=====
Composition/Information on Ingredients
=====

Ingred Name:PARAFFIN WAX

CAS:8002-74-2

RTECS #:RV0350000

Fraction by Wt: 40.5%

OSHA PEL:2 MG/M3 (FUME)

ACGIH TLV:2 MG/M3 (FUME); 9192

Ingred Name:NAPHTHENES

Fraction by Wt: 52.2%

Ingred Name:OLEFINS

Fr

action by Wt: 0.5%

Ingred Name:AROMATICS (C*8)

Fraction by Wt: 6.8%

=====
Hazards Identification
=====

Effects of Overexposure:VAP: INTOXICATING, NARCOTIC, IRRIT TO MUCOUS
MEMBRANES OF LUNGS. LIQ: HARMFUL &/OR FATAL IF INGESTED

=====
First Aid Measures
=====

First Aid:VAP: REMOVE VICTIM FROM CONTAM AREA. KEEP WARM & QUIET. IF
BRTHNG HAS STOPPED, GIVE ARTIF RESP. IF SWALLOWED: DO NOT INDUCE
VOMITING. CALL PHY
SICIAN IMMED. AVOID FREQUENT AND/OR PROLONGED
CONTACT W/SK IN.

=====
Fire Fighting Measures
=====

Flash Point:100F CC

Lower Limits:1.1

Upper Limits:6.1

Extinguishing Media:CO*2, DRY CHEMICAL, FOAM OR OTHER MEDIA FOR CLASS B
FIRES

=====
Accidental Release Measures
=====

Spill Release Procedures:MATERIA L IS FLAMMABLE & CARE SHOULD BE
EXERCISED TO PREVENT FIRE. SPILLED MATERIAL MAY BE PUMPED INTO
ANOTHER CONTAINER, O
R ABSORBED & REMOVED FROM THE AREA. ALL SPARKS,
FLAMES & IGNITION SOURCES SHO ULD BE KEPT OUT OF AREA. NON-SPARKING
TOOLS NEEDED

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINER CLOSED. DO NOT STORE OR
USE NEAR HEAT, SPARKS OR FLAME. KEEP IN A COOL, DRY PLACE.

Other Precautions:GROUND ALL CONTAINERS WHEN TRANSFERRING LIQUID. AVOID
PROLONGED CONTACT W/LIQUID &/OR VAPOR. USE NON-SPARKING TOOLS.

=====
Exp

osure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD SELF-CONTAINED OR SUPPLY AIR MASKS IF VAPOR CONC.

Ventilation:MFR RECM LOCAL EXHST,MECH, SPEC IF VAP HEAVY

Protective Gloves:RUBBER, PLASTIC

Eye Protection:YES

Supplemental Safety and Health

MFR STATES THIS PRODUCT ALSO MEETS FED. SPEC. P-D-680, TYI.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:305-395F

Vapor Pres:5.

Vapor Density:4.83

Spec Gravity

:0.776

Evaporation Rate & Reference:4L (ETHYL ETHER)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WATER WHITE LIQ; MILD SWEET NAPHTHA ODOR

Percent Volatiles by Volume:>99.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:STABLE UNDER MOST CONDITIONS.

EXPLO/COMBUST MIX W/AIR/OXY

Hazardous Decomposition Products:COMBUSTION PRODUCTS ARE CO*2 & WATER

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECM INCINERATION. DISPOSE IN ACCORDANCE W/FED., STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek compete

nt professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.